



// ONE BRAND // ONE SOURCE // ONE SYSTEM

REMALINE 40 ORANGE - Universal Lining for many applications

REMA TIP TOP's high-quality REMALINE lining offers optimum surface protection for your machinery and equipment while minimizing production downtime, reducing maintenance costs, and increasing productivity.

APPLICATION AREAS

REMALINE 40 ORANGE has been designed for a variety of wet or dry applications. In dry applications, REMALINE 40 ORANGE is frequently used in abrasion applications for processing sand and gravel. In wet applications, this material has proven its outstanding worth as a protective coating against sharp particles thanks to its high resistance to tearing. REMALINE 40 ORANGE also features excellent qualities for eliminating bridge formation and build-up.

TYPICAL FIELDS OF USE

- Pipe linings, launders, pumps, cyclones, discharge boots, flotation cells, non-driven pulleys
- Cut and impact wear in wet and dry applications

ADVANTAGES

- Protection against sharp material
- Universal applications
- Easy and fast installation
- Increases the efficiency of your equipment
- Technical consultation and data available anytime



REMALINE 40 ORANGE

TECHNICAL PROPERTIES

Product Characteristics	REMALINE 40 ORANGE is a natural rubber based product for a wide range of applications.	
	CN bonding layer: REMALINE 40 ORANGE comes equipped with a CN bonding layer, which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.	
Storage Stability	Max. 24 months At 77°F ± 3.6°F with no loss in quality Subject to DIN regulation 7716	
Color		Orange
Polymer	DIN ISO 1629	NR
Hardness	DIN ISO 7619-1	44 Shore A
Abrasion	DIN ISO 4649	140 (5N) mm ³
Specific Weight	DIN EN ISO 1183-1	1.05 g/cm ³ (65.55 lb/ft ³)
Tensile Strength	DIN 53 504	26 N/mm ²
Elongation at break	DIN 53 504	650%
Resilience Elasticity	DIN 53 512	80%
Tear Growth Resistance	ISO 34-1 Method A	7 N/mm
Available sizes*	Standard thickness	1/8", 1/4", 3/8", 1/2", 3/4", 1"
	Standard width	5', 6½'

*Other sizes available on request. REMALINE 40 ORANGE is also available with fabric reinforcement.

REMA TIP TOP/North America, Inc.

1500 Industrial Blvd. • Madison, GA 30650 • Phone 800.334.REMA (7362) • 706.752.4000 • Fax 706.752.4015 → www.rematiptop.com