



// ONE BRAND // ONE SOURCE // ONE SYSTEM



**T-REX 40 RUBBER LINING**  
Value & Quality for  
Common Applications  
**Call for Site Consultation**

// SERVICE // MATERIAL PROCESSING // SURFACE PROTECTION // AUTOMOTIVE

## T-REX 40 Rubber Lining

### Applications Areas:

The properties of T-REX 40 Rubber Lining make it an excellent value Lining for the Sand and Gravel Industry. It features good resistance to wet abrasive and sharp particles. It is also valuable when used in sticky applications to reduce material build up.

**Call 800-334-7362**

for Application Recommendations

# T-REX 40 Rubber Lining

## Product Characteristics

T-REX 40 is a rubber material based on natural rubber offering universal applications. T-REX 40 comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.

### TYPICAL FIELDS OF USE:

- Wash Plants
- Screen Decks
- Sand Flumes
- Non Driven Pulleys (Build up Protection)

### ADVANTAGES:

- Competitively Priced
- Easy Installation
- Universal Applications
- Increased Plant Efficiency
- Superior Technical Support

Description	T-REX 40 Sheet Rubber
Part Numbers	101064003, 10106400, 101064010, 101064012
Color	Red
Roll Size	78" x 33' (1/8", 1/4", 3/8", 1/2")

PROPERTY/TEST	STANDARD	UNIT	
Color	-	-	Red
Elastometer			NR
Shore Hardness	DIN ISO 7619-1	Shore A	40 ± 5
Tensile Strength	DIN 53504	MPA	22
Elongation at break	DIN 53504	%	>500
Density	DIN EN ISO 1183	g/cm <sup>3</sup>	1.04
Abrasion	DIN ISO 4649	mm <sup>3</sup>	<160



// ONE BRAND // ONE SOURCE // ONE SYSTEM

REMA TIP TOP/North America, Inc.  
 1500 Industrial Blvd.  
 Madison, GA 30650  
 Phone 800.334.REMA (7362)  
 706.752.4000  
 Fax 706.752.4015  
[www.rematiptop.com](http://www.rematiptop.com)