



// ONE BRAND // ONE SOURCE // ONE SYSTEM



REMASKIRT 50

Conveyor Skirt Board Rubber

REMASKIRT 50 - Conveyor Skirt Board Rubber

LONGER LASTING PERFORMANCE

- Less maintenance dollars spent on skirt board rubber replacement.

BETTER CONTAINMENT AND SEALING

- REMASKIRT 50 is a natural rubber compound with 4206 psi tensile strength and a Shore A Hardness of 50.
- The softer style rubber provides excellent sealing against your conveyor belting to contain material and help reduce dust.

REDUCED BELT WEAR

- Since REMASKIRT 50 is a softer rubber, compared to conventional skirting, it greatly reduces wear in the top cover of your conveyor belt.

PROPERTIES

- Low friction
- Easy fitment
- Available in thicknesses from ¼" to 1" and belt widths of 70.4" and 78"
- Special qualities available on request
- Designed for temperatures from -40°F to +176°F

AREA OF APPLICATION

- Skirting rubber and scraper for wet, sticky material

TECHNICAL DATA

Color	Orange	
Rubber	NR	DIN ISO 1629
Hardness	51 Shore A	DIN ISO 7619-1
Abrasion	160 mm ³	DIN ISO 4649
Density	1.11 g/cm ³ (69.30 lb/ft ³)	DIN EN ISO 1183-1
Tensile Strength	27 N/mm ² (3916 psi)	DIN 53 504
Elongation at break	600%	DIN 53 504
Resilience	70%	DIN 53 512
Tear Growth Resistance	15 N/mm (0.097 Lbf/in)	ISO 34-1 Methode A

REMA TIP TOP/North America, Inc.

1500 Industrial Blvd. • Madison, GA 30650 • Phone 800.334.REMA (7362) • 706.752.4000 • Fax 706.752.4015 → www.rematiptop.com