

Premium quality for wet wear and build-up

# REMALINE 35

Our high-quality **REMALINE** lining offers optimum surface protection for your machines and equipment. You avoid unnecessary costs for maintenance and downtime, thereby increasing the productivity of your equipment many times over.

## Application areas

**REMALINE 35** features excellent resistance to wet abrasive and sharp particles. The properties of **REMALINE 35** make it the optimum rubber lining for sand and gravel industry equipment as well as in the glass industry. **REMALINE 35** lining has also proven valuable with sticky material such as loam and clay.



Pipe lining



## Typical fields of use

- Pipe lining
- Pumps
- Slides, gutters and aprons
- Loader bucket lining to prevent build-up
- Outlet hoses for ready-mix concrete

## Advantages

- Build-up elimination
- Less noise in your equipment
- Easy and fast installation
- Technical consultation and data available anytime
- ▶ **Increases the efficiency of your equipment**

Premium quality for wet wear and build-up

# REMALINE 35



Industrie

## Technical properties

<b>Product characteristics</b>	<b>REMALINE 35</b> is a material with extraordinarily high elasticity and stretching properties, consisting of 95 % natural rubber.	
	CN bonding layer: <b>REMALINE 35</b> comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the <b>REMA TIP TOP</b> adhesive systems.	
<b>Storage stability</b>	Max. 24 months ▶ At 25 °C ± 2 °C with no loss in quality. Subject to DIN regulation 7716.	
<b>Color</b>		yellow
<b>Polymer</b>	DIN ISO 1629	NR
<b>Specific weight</b>	DIN EN ISO 1183	0,96 g/cm <sup>3</sup>
<b>Hardness</b>	ISO 868-2003 (DIN 53505)	34 ± 5 Shore A
<b>Abrasion at 5 N</b>	DIN ISO 4649-2006	110 mm <sup>3</sup>
<b>Resilience elasticity</b>	ISO 4462-1986 (DIN 53512)	78 %
<b>Available sizes*</b>	Standard thickness in mm	3 - 25
	Standard width in mm	1 500 or 2 000

\*Other dimensions available on request.

**REMALINE 35** is also available with fabric reinforcement.

### REMA TIP TOP/North America Inc Industrial Division

1500 Industrial Blvd.  
Madison, GA 30650

Toll Free: 800.334.REMA (7362)

Phone: 706.752.4000

Fax: 706.752.4015

[www.rematiptop.com](http://www.rematiptop.com)

ONE BRAND – ONE SOURCE – ONE SYSTEM

