

The universal lining for many applications

# REMALINE 40

Our high-quality **REMALINE** lining offers optimum surface protection for your machines and equipment. You avoid unnecessary costs for maintenance and downtime, thereby increasing the productivity of your equipment many times over.

## Application areas

**REMALINE 40** has been designed for a variety of wet or dry applications. In dry applications, **REMALINE 40** is frequently used for conveying coke. In wet applications, this material has proven its outstanding worth as a protective coating for sharp particles thanks to its high resistance to tearing. **REMALINE 40** also features excellent qualities for eliminating bridge formation and build-up.



## Typical fields of use

- Hydrocyclones
- Bucket lining for conveying wet loam/clay
- Coating for non-driven pulleys with low belt tensions (build-up protection)
- Flexilo and bunker lining

## Advantages

- Protection against damage caused by sharp material
- Universal applications
- Easy and fast installation
- Technical consultation and data available anytime
- ▶ **Increases the efficiency of your equipment**

The universal lining for many applications

# REMALINE 40



Industrie

## Technical properties

<b>Product characteristics</b>	<b>REMALINE 40</b> is a rubber material based on natural rubber offering universal applications.	
	CN bonding layer: <b>REMALINE 40</b> comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the <b>REMA TIP TOP</b> adhesive systems.	
<b>Storage stability</b>	Max. 24 months ▶ At 25 °C ± 2 °C with no loss in quality. Subject to DIN regulation 7716.	
<b>Color</b>		orange
<b>Polymer</b>	DIN ISO 1629	NR
<b>Specific weight</b>	DIN EN ISO 1183	1,02 g/cm <sup>3</sup>
<b>Hardness</b>	ISO 868-2003 (DIN 53505)	40 ± 5 Shore A
<b>Abrasion</b>	DIN ISO 4649-2006	140 mm <sup>3</sup>
<b>Resilience elasticity</b>	ISO 4462-1986 (DIN 53512)	75 %
<b>Available sizes*</b>	Standard thickness in mm	3 - 20
	Standard width in mm	1 500 or 2 000
<b>Special qualities</b>	<ul style="list-style-type: none"><li>▶ Oil- and grease-resistant</li><li>▶ Highly flame-retardant (<b>REMALINE 40 „S“</b>)</li><li>▶ Heat-resistant (<b>REMALINE 40 HR</b>)</li><li>▶ Certified food-safe (FDA, Cat. 3 + 4 of BGVV)</li></ul>	

\*Other dimensions available on request.

**REMALINE 40** is also available with fabric reinforcement.

### REMA TIP TOP/North America Inc Industrial Division

1500 Industrial Blvd.  
Madison, GA 30650

Toll Free: 800.334.REMA (7362)

Phone: 706.752.4000

Fax: 706.752.4015

www.rematiptop.com

ONE BRAND – ONE SOURCE – ONE SYSTEM

