

The lining for protection from impact wear

REMALINE 60

Our high-quality **REMALINE** lining offers optimum surface protection for your machines and equipment. You avoid unnecessary costs for maintenance and downtime, thereby increasing the productivity of your equipment many times over.

Application areas

Thanks to its low-abrasion properties, **REMALINE 60** is especially suitable for protecting against impact and dry wear and, based on this, is frequently used for conveying coal. Furthermore, non-driven pulleys can be vulcanized with **REMALINE 60**.



Transfer point



Typical fields of use

- Lining for vibration feeders, slides, bunkers, chutes and sieve tubs
- Coating of idler, constriction and bending pulleys for medium to high belt tensions

Advantages

- Protection from impact wear abrasion caused by dry, sharp-edged material
- Easy and fast installation
- Technical consultation and data available anytime
- ▶ **Increases the efficiency of your equipment**

The lining for protection from impact wear

REMALINE 60

Technical properties

Product characteristics	REMALINE 60 is a mixture of styrene, butadiene and isoprene rubber with good wear resistance against dry wear and impact.	
	CN bonding layer: REMALINE 60 comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.	
Storage stability	Max. 24 months ▶ At 25 °C ± 2 °C with no loss in quality. Subject to DIN regulation 7716.	
Color		black
Polymer	DIN ISO 1629	BR/IR/SBR
Specific weight	DIN EN ISO 1183	1,13 g/cm ³
Hardness	ISO 868-2003 (DIN 53505)	60 ± 5 Shore A
Abrasion	DIN ISO 4649-2006	90 mm ³
Resilience elasticity	ISO 4462-1986 (DIN 53512)	45 %
Available sizes*	Standard thickness in mm	3 - 50
	Standard width in mm	1 500 or 2 000

*Other dimensions available with fabric reinforcement.

REMALINE 60 is also available with fabric reinforcement.

**REMA TIP TOP/North America Inc
Industrial Division**

1500 Industrial Blvd.
Madison, GA 30650

Toll Free: 800.334.REMA (7362)

Phone: 706.752.4000

Fax: 706.752.4015

www.rematiptop.com

ONE BRAND – ONE SOURCE – ONE SYSTEM

