

Premium quality for extreme wear situations

REMALINE 70

Our high-quality **REMALINE** lining offers optimum surface protection for your machines and equipment. You avoid unnecessary costs for maintenance and downtime, thereby increasing the productivity of your equipment many times over.

Application areas

REMALINE 70, a material featuring especially excellent resistance to abrasion. **REMALINE 70** is the material of choice for applications with extremely high wear and impact. Thanks to its high tear resistance and tensile strength, **REMALINE 70** is especially suitable for equipment used to convey large-particle, broken and sharp-edged material.



Typical fields of use

- Bunker lining
- Material transfer stations
- Truck load surface lining
- Mill lining
- Chute, gutter and funnel lining
- Coating for pulleys with high belt tension

Advantages

- Protection against extreme wear and impact
- Unmatched abrasion resistance
- Easy and fast installation
- Technical consultation and data available anytime
- ▶ **Increases the efficiency of your equipment**

Premium quality for extreme wear situations

REMALINE 70



Technical properties

Product characteristics	REMALINE 70 is a mixture of isoprene and butadiene rubber featuring excellent abrasion resistance.	
	CN bonding layer: REMALINE 70 comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.	
Storage stability	Max. 24 months ▶ At 25 °C ± 2 °C with no loss in quality. Subject to DIN regulation 7716.	
Color		black, white
Polymer	DIN ISO 1629	NR/BR
Specific weight	DIN EN ISO 1183	1,10 g/cm ³
Hardness	ISO 868-2003 (DIN 53505)	64 ± 5 Shore A
Abrasion	DIN ISO 4649-2006	50 mm ³
Resilience elasticity	ISO 4462-1986 (DIN 53512)	51 %
Available sizes*	Standard thickness in mm	3 - 50
	Standard width in mm	1 500 or 2 000
Special qualities	<ul style="list-style-type: none">▶ Oil- and grease-resistant▶ Self-extinguishing for underground mining (REMALINE 70 „V“)▶ Highly flame-retardant (REMALINE 70 „S“)▶ Heat-resistant (REMALINE 70 HR)▶ Certified food-safe (FDA, Cat. 3 + 4 for BGVV)	

*Other dimensions available on request.

REMA TIP TOP/North America Inc
Industrial Division
1500 Industrial Blvd.
Madison, GA 30650
Toll Free: 800.334.REMA (7362)
Phone: 706.752.4000
Fax: 706.752.4015
www.rematiptop.com

ONE BRAND – ONE SOURCE – ONE SYSTEM

