

REMA TIP TOP/North America Inc

Chicago Pneumatic™

TIRE BUFFERS



Automotive



HIGH SPEED TIRE BUFFER - CP-871

FEATURES AND BENEFITS:

- Jacobs chuck for holding buffing accessories
- Safety-lock throttle to prevent accidental start up
- Convenient rear exhaust directs air away from work area
- Trigger throttle allows adjustment of speed to match job applications
- Ideal for trimming steel cables and cleaning tire cavities

SPECIFICATIONS

Wheel Size	3/8"
Free Speed	22,000 rpm
Weight	1-3/4 lbs.
Length	8"
Average Air Consumption	13 cfm
Actual Air Consumption	26 cfm
Air Inlet Thread	1/4" NPTF
Min. Hose Size	3/8"

LOW SPEED TIRE BUFFER - CP-873K

FEATURES AND BENEFITS:

- Quick change chuck for fast and easy change of buffing wheels
- Safety-lock throttle to prevent accidental start up
- Convenient rear exhaust directs air away from work area
- Trigger throttle allows adjustment of speed to match job applications
- Ideal for tire repair work, texturizing the repair area for recapping and cleaning tire moldings

SPECIFICATIONS

Wheel Size	7/16"
Free Speed	2,800 rpm
Weight	2-1/4 lb.
Length	8-1/4"
Average Air Consumption	13 cfm
Actual Air Consumption @ load	26 cfm
Air Inlet Thread Size	1/4" NPTF
Min. Hose Size	3/8"



We supply your workshop

ONE BRAND – ONE SOURCE – ONE SYSTEM

REMA TIP TOP / North America, Inc.
Automotive Division

119 Rockland Avenue • Northvale, NJ 07647
Phone: 800-225-REMA • www.rematiptop.com