



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Name: Tip Top Primer HG 1
 Product Use: Primer Coat
 MSDS Preparation Date: 3/21/2006
 Manufacturer: REMA TIP TOP/NO. AMERICA, 119 Rockland Avenue, Northvale, NJ 07647
 24-Hour Emergency Phone Number: 800-424-9300 (CHEMTREC)

2. PRODUCT INGREDIENTS

<u>CHEMICAL NAME:</u>	<u>CAS NUMBER:</u>	<u>% RANGE:</u>	<u>OSHA PEL:</u>
Methylisobutyl ketone	108-10-1	50-60	100 ppm TWA; 410 mg/m ³ TWA
Xylenes (o-, m-, p- isomers)	1330-20-7	5-10	100 ppm TWA; 435 mg/m ³ TWA
Ethyl benzene	100-41-4	1-5	100 ppm TWA; 435 mg/m ³ TWA
Phenol	108-95-2	1-2	5 ppm TWA; 19 mg/m ³ TWA

The balance of ingredients not rated as hazardous as defined in 29 CFR 1910.1200.

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

This product is regulated under the Canadian Controlled Products Regulations.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

The product is a grey liquid. This product is a flammable liquid and vapor. Vapors may cause flash fire. It can cause eye, skin, respiratory and digestive system irritation. Repeated exposure may cause skin dryness or cracking. Harmful by inhalation, in contact with skin and if swallowed. A component is an aspiration hazard. Symptoms of exposure may include central nervous system depression. Contains a suspect carcinogen.

EYE: This product may cause irritation to the eyes. Symptoms may include burning, redness, and tearing.

SKIN: This product is irritating to the skin. Prolonged and/or repeated skin contact with this product may cause irritation, defatting of skin and dermatitis. Components may be absorbed through the skin.

INGESTION: Harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. May produce central nervous system depression. If aspirated (liquid enters the lung), the product may be rapidly absorbed through the lungs.

INHALATION: This product may be harmful by inhalation. This product may cause respiratory system irritation causing symptoms that may include: dryness of the throat, tightness of the chest, and shortness of breath. May cause CNS depression characterized by the following: headache, dizziness, staggering gait, confusion, unconsciousness, or coma.



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

4. FIRST AID

EYES: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.

SKIN: For skin contact flush with large amounts of water while removing contaminated clothing. Wash affected area with mild soap and water. If irritation persists, get medical attention. Wash contaminated clothing before reuse. Contaminated leather articles, including shoes, that cannot be decontaminated should be discarded.

INGESTION: Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a physician immediately.

INHALATION: If inhaled, immediately remove the affected person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.

NOTE TO PHYSICIAN: Provide general supportive measures and treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point: 17°C (62.6°F)

Upper Flammable Limit (UFL): 9%

Auto Ignition: 460°C (860°F)

Method Used: Not Available

Lower Flammable Limit (LFL): 1.7%

Flammability Classification: Class IB Flammable Liquid

HAZARDOUS COMBUSTION PRODUCTS: Decomposition products may include and are not limited to carbon monoxide and carbon dioxide, hydrogen chloride and irritating, corrosive, toxic or flammable gases.

EXTINGUISHING MEDIA: Water fog/fine spray, carbon dioxide, foam, and dry chemical.

FIRE FIGHTING INSTRUCTIONS: This product is a Class IB flammable liquid. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.

PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

6. ACCIDENTAL RELEASE MEASURES

CONTAINMENT PROCEDURES: Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Handling equipment must be grounded to prevent sparking. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

CLEAN-UP PROCEDURES: Wear appropriate protective equipment and clothing during clean-up. Eliminate ignition sources including sources of electrical, static or frictional sparks. Ventilate the contaminated area. Absorb spill with inert material. Shovel material into properly labeled closed metal containers for disposal. Use non-sparking tools. Place in non-leaking containers for immediate disposal. Flush area with water to remove trace residue. Do not allow the spilled product to enter public drainage system or open water courses.



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

EVACUATION PROCEDURES: Persons not wearing appropriate protective equipment should be excluded from area of spill until clean up has been completed.

SPECIAL PROCEDURES: Follow all Local, State, Federal and Provincial regulations for disposal.

7. HANDLING & STORAGE

HANDLING: Keep liquid and vapor away from heat, sparks and flames. Surfaces that are sufficiently hot may ignite liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash fire can result. Keep containers closed when not in use. Use with adequate ventilation.

Containers, even those that have been emptied, can contain explosive vapors. DO NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT pressurize drum containers to empty them.

Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment.

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Air-dry contaminated clothing in a well ventilated area before laundering.

STORAGE: Keep packaged in original, labeled containers until use. Store in a cool, dry, well-ventilated area. Store this product in air-tight containers away from sources of heat and light. Ground all equipment to prevent accumulation of static charge. Store away from incompatible materials. Do not remove or deface label. Do not reuse container without recycling or reconditioning in accordance with any Federal, Provincial, State or local laws. Do not use cutting or welding torches, open flames, or electric arcs on empty or full containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION: Wear safety glasses. Chemical goggles and/ or face shields should be worn, when splashing is a possibility. Contact lenses should not be exposed. If vapor exposure causes eye discomfort, use a full-face respirator.

SKIN PROTECTION: Use impervious gloves. Use of impervious apron and boots are recommended.

RESPIRATORY PROTECTION: If recommended exposure limits are exceeded, a NIOSH-approved, continuous flow supplied air-respirator, hood or helmet is acceptable. A NIOSH approved self-contained positive pressure breathing apparatus, with full-face piece, is required for spills and/ or emergencies.

EXPOSURE GUIDELINE(s):



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

Component Exposure Limits

REMA TIP/TOP USA recommends that its customers minimize employee exposure. REMA therefore suggests that its customers consider adopting the lower of the current OSHA PEL or the ACGIH TLV's for the purpose of evaluating employee exposures. The TLV's recommended by the ACGIH have been updated on a continuing basis.

Methylisobutyl ketone (108-10-1)

ACGIH: 50 ppm TWA
75 ppm STEL
OSHA: 100 ppm TWA; 410 mg/m³ TWA
NIOSH: 50 ppm TWA; 205 mg/m³ TWA
75 ppm STEL; 300 mg/m³ STEL

Xylenes (o-, m-, p- isomers) (1330-20-7)

ACGIH: 100 ppm TWA
150 ppm STEL
OSHA: 100 ppm TWA; 435 mg/m³ TWA

Ethyl benzene (100-41-4)

ACGIH: 100 ppm TWA
125 ppm STEL
OSHA: 100 ppm TWA; 435 mg/m³ TWA
NIOSH: 100 ppm TWA; 435 mg/m³ TWA
125 ppm STEL; 545 mg/m³ STEL

Phenol (108-95-2)

ACGIH: 5 ppm TWA
Skin - potential significant contribution to overall exposure by the cutaneous route
OSHA: 5 ppm TWA; 19 mg/m³ TWA
prevent or reduce skin absorption
NIOSH: 5 ppm TWA; 19 mg/m³ TWA
15.6 ppm Ceiling (15 min); 60 mg/m³ Ceiling (15 min)
Potential for dermal absorption

Component Exposure Limits - Canada

The following Provincial Exposure Limits apply for this product's components.

Methylisobutyl ketone (108-10-1)

Alberta: 50 ppm TWA; 205 mg/m³ TWA
75 ppm STEL; 307 mg/m³ STEL
British Columbia: 50 ppm TWA
75 ppm STEL
Manitoba: 50 ppm TWA; 205 mg/m³ TWA
75 ppm STEL; 300 mg/m³ STEL
New Brunswick: 50 ppm TWA; 205 mg/m³ TWA
75 ppm STEL; 307 mg/m³ STEL
NW Territories: 50 ppm TWA; 205 mg/m³ TWA
75 ppm STEL; 300 mg/m³ STEL
Nova Scotia: 50 ppm TWA
75 ppm STEL
Nunavut: 50 ppm TWA; 205 mg/m³ TWA
75 ppm STEL; 300 mg/m³ STEL
Ontario: 50 ppm TWAEV; 205 mg/m³ TWAEV
75 ppm STEV
Quebec: 50 ppm TWAEV; 205 mg/m³ TWAEV
75 ppm STEV; 310 mg/m³ STEV
Saskatchewan: 205 mg/m³ TWA; 50 ppm TWA



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

	307 mg/m3 STEL; 75 ppm STEL
Yukon:	100 ppm TWA; 410 mg/m3 TWA 125 ppm STEL; 510 mg/m3 STEL
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Alberta:	100 ppm TWA; 434 mg/m3 TWA 150 ppm STEL; 651 mg/m3 STEL
British Columbia:	100 ppm TWA 150 ppm STEL
Manitoba:	100 ppm TWA; 435 mg/m3 TWA 150 ppm STEL; 655 mg/m3 STEL
New Brunswick:	100 ppm TWA; 434 mg/m3 TWA 150 ppm STEL; 651 mg/m3 STEL
NW Territories:	100 ppm TWA; 434 mg/m3 TWA 150 ppm STEL; 652 mg/m3 STEL
Nova Scotia:	100 ppm TWA 150 ppm STEL
Nunavut:	100 ppm TWA; 434 mg/m3 TWA 150 ppm STEL; 652 mg/m3 STEL
Ontario:	100 ppm TWAEV; 435 mg/m3 TWAEV 150 ppm STEV; 650 mg/m3 STEV
Quebec:	100 ppm TWAEV; 434 mg/m3 TWAEV 150 ppm STEV; 651 mg/m3 STEV
Saskatchewan:	434 mg/m3 TWA; 100 ppm TWA 651 mg/m3 STEL; 150 ppm STEL
Yukon:	100 ppm TWA; 435 mg/m3 TWA 150 ppm STEL; 650 mg/m3 STEL
Ethyl benzene (100-41-4)	
Alberta:	100 ppm TWA; 434 mg/m3 TWA 125 ppm STEL; 543 mg/m3 STEL
British Columbia:	100 ppm TWA 125 ppm STEL
Manitoba:	100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
New Brunswick:	100 ppm TWA; 434 mg/m3 TWA 125 ppm STEL; 543 mg/m3 STEL
NW Territories:	100 ppm TWA; 434 mg/m3 TWA 125 ppm STEL; 542 mg/m3 STEL
Nova Scotia:	100 ppm TWA 125 ppm STEL
Nunavut:	100 ppm TWA; 434 mg/m3 TWA 125 ppm STEL; 542 mg/m3 STEL
Ontario:	100 ppm TWAEV; 435 mg/m3 TWAEV 125 ppm STEV; 540 mg/m3 STEV
Quebec:	100 ppm TWAEV; 434 mg/m3 TWAEV 125 ppm STEV; 543 mg/m3 STEV
Saskatchewan:	435 mg/m3 TWA; 100 ppm TWA 543 mg/m3 STEL; 125 ppm STEL
Yukon:	100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
Phenol (108-95-2)	



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

Alberta:	5 ppm TWA; 19 mg/m ³ TWA
British Columbia:	5 ppm TWA
Manitoba:	5 ppm TWA; 19 mg/m ³ TWA
New Brunswick:	5 ppm TWA; 19 mg/m ³ TWA
NW Territories:	5 ppm TWA; 19 mg/m ³ TWA 10 ppm STEL; 38 mg/m ³ STEL
Nova Scotia:	5 ppm TWA
Nunavut:	5 ppm TWA; 19 mg/m ³ TWA 10 ppm STEL; 38 mg/m ³ STEL
Ontario:	5 ppm TWAEV; 19 mg/m ³ TWAEV
Quebec:	5 ppm TWAEV; 19 mg/m ³ TWAEV
Saskatchewan:	19 mg/m ³ TWA; 5 ppm TWA 29 mg/m ³ STEL; 7.5 ppm STEL
Yukon:	5 ppm TWA; 19 mg/m ³ TWA 10 ppm STEL; 38 mg/m ³ STEL

9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE: Grey liquid

ODOR: Characteristic **ODOR THRESHOLD:** Not Available

BOILING POINT: 116°C (240.8°F)

SOLUBILITY IN WATER: Insoluble

SPECIFIC GRAVITY: 0.92-0.94 g/ml @ 20°C (68°F)

VAPOR PRESSURE: 7-9 mbar @ 20°C (68°F)

% VOLATILE: 90%

10. STABILITY & REACTIVITY

INCOMPATIBILITY WITH OTHER MATERIALS: Materials to avoid are strong acids, bases, and oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

DECOMPOSITION PRODUCTS: Decomposition products may include and are not limited to carbon monoxide and carbon dioxide, hydrogen chloride and irritating, corrosive, toxic or flammable gases.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

This product is harmful by inhalation, when in contact with the skin, eyes and if it is swallowed. Aspiration hazard. Lung damage may occur if aspirated into the lungs and may be fatal. Symptoms include coughing and difficulty breathing. May cause CNS effects with symptoms that include headache, drowsiness, dizziness and loss of coordination. Inhalation of high vapor concentrations may cause symptoms of headache, dizziness, drowsiness, nausea and vomiting.



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

CHRONIC TOXICITY

Overexposure may cause damage to the liver and kidneys. Repeated or prolonged exposure may cause skin irritation and dermatitis.

CARCINOGENICITY

Ethylene benzene has demonstrated evidence of carcinogenicity in animals.

Component Carcinogenicity

Xylenes (o-, m-, p- isomers) (1330-20-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71, 1999; Monograph 47, 1989 (Group 3 (not classifiable))

Ethyl benzene (100-41-4)

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans

IARC: Monograph 77, 2000 (Group 2B (possibly carcinogenic to humans))

Phenol (108-95-2)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71, 1999; Monograph 47, 1989 (Group 3 (not classifiable))

12. ECOLOGICAL INFORMATION

No information available for the product. Contains components harmful to aquatic life.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Methylisobutyl ketone (108-10-1)

Test & Species

		Conditions
96 Hr LC50 Pimephales promelas	505 mg/L [flow-through]	
96 Hr EC50 Selenastrum capricornutum	400 mg/L	
5 min EC50 Photobacterium phosphoreum	79.6 mg/L	
24 Hr EC50 water flea	4280.0 mg/L	
48 Hr EC50 Daphnia magna	170 mg/L	

Xylenes (o-, m-, p- isomers) (1330-20-7)

Test & Species

		Conditions
96 Hr LC50 Pimephales promelas	13.4 mg/L [flow-through]	
96 Hr LC50 Oncorhynchus mykiss	8.05 mg/L [flow-through]	
96 Hr LC50 Lepomis macrochirus	16.1 mg/L [flow-through]	
96 Hr LC50 Pimephales promelas	26.7 mg/L [static]	
24 hr EC50 Photobacterium phosphoreum	0.0084 mg/L	
48 Hr EC50 water flea	3.82 mg/L	
48 Hr LC50 Gammarus lacustris	0.6 mg/L	

Ethyl benzene (100-41-4)

Test & Species

		Conditions
96 Hr LC50 Oncorhynchus mykiss	14.0 mg/L [static]	
96 Hr LC50 Pimephales promelas	9.09 mg/L [flow-through]	
96 Hr LC50 Lepomis macrochirus	150.0 mg/L [static]	
96 Hr LC50 Oncorhynchus mykiss	4.2 mg/L [static]	
96 Hr LC50 Lepomis macrochirus	32 mg/L [static]	
96 Hr LC50 Pimephales promelas	48.5 mg/L [static]	
96 Hr LC50 Poecilia reticulata	9.6 mg/L [static]	



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

72 Hr EC50 Selenastrum capricornutum	4.6 mg/L
96 Hr EC50 Selenastrum capricornutum	>438 mg/L
30 min EC50 Photobacterium phosphoreum	9.68 mg/L
24 Hr EC50 Nitrosomonas	96 mg/L
48 Hr EC50 Daphnia magna	1.8-2.4 mg/L

Phenol (108-95-2)

Test & Species

Test & Species	Conditions
96 Hr LC50 Pimephales promelas	24 mg/L [flow-through]
96 Hr LC50 Oncorhynchus mykiss	8.9 mg/L [flow-through]
96 Hr LC50 Lepomis macrochirus	23.88 mg/L [static]
96 Hr LC50 Oncorhynchus mykiss	5-12 mg/L [flow-through]
96 Hr LC50 Poecilia reticulata	40 mg/L [static]
96 Hr LC50 Brachydanio rerio	27.8 mg/L
96 Hr EC50 Selenastrum capricornutum	150 mg/L
5 min EC50 Photobacterium phosphoreum	28.8 mg/L
15 min EC50 Photobacterium phosphoreum	31.6 mg/L
5 min EC50 Photobacterium phosphoreum	23.28 mg/L
15 min EC50 Photobacterium phosphoreum	25.61 mg/L
30 min EC50 Photobacterium phosphoreum	21-36 mg/L
48 Hr EC50 water flea	23.0 mg/L
48 Hr LC50 Daphnia magna	13 mg/L

13. DISPOSAL CONSIDERATIONS

DISPOSAL: Waste must be handled in accordance with all federal, state, provincial, and local regulations.

UNUSED & UNCONTAMINATED PRODUCT:

Component Waste Numbers

Methylisobutyl ketone (108-10-1)

RCRA: waste number U161 (Ignitable waste)

Xylenes (o-, m-, p- isomers) (1330-20-7)

RCRA: waste number U239 (Ignitable waste, Toxic waste)

Phenol (108-95-2)

RCRA: waste number U188

If discarded, this product is considered a RCRA ignitable waste, D001.

14. TRANSPORT INFORMATION



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

US DOT Information

Shipping Name: Paint

UN/NA #: UN1263 **Hazard Class:** 3 **Packing Group:** II

Required Label(s): FLAMMABLE LIQUID

Additional Info.: PLACARD (WHEN REQUIRED): FLAMMABLE, 3.

EXCEPTIONS: DOT Paragraphs 173.150, 173.173, & 173.242.

ALTERNATE SHIPPING ARRANGEMENTS: Based on package or shipping container size, this product may be shipped as a, "Limited Quantity", or, renamed, "Consumer Commodity" and reclassified as, "ORM-D" Material.

TDG Information

Shipping Name: Paint

UN/NA #: UN1263 **Hazard Class:** 3 **Packing Group:** II

Required Label(s): FLAMMABLE Liquid

IMDG Information

Additional Info.:F-E, S-E

IATA Information

Additional Info.: 3

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

SARA 313 INFORMATION:

Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 313 (40 CFR 372.65).

Methylisobutyl ketone (108-10-1)

SARA 313: 1.0 % de minimis concentration

Xylenes (o-, m-, p- isomers) (1330-20-7)

SARA 313: 1.0 % de minimis concentration

Ethyl benzene (100-41-4)

SARA 313: 0.1 % de minimis concentration

Phenol (108-95-2)

SARA 313: 1.0 % de minimis concentration

SARA HAZARD CATEGORY:

Acute Health: Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactive:** No

COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA):



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

Component Analysis

This material contains one or more of the following chemicals required to be identified under CERCLA (40 CFR 302.4).

Methylisobutyl ketone (108-10-1)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Xylenes (o-, m-, p- isomers) (1330-20-7)

CERCLA: 100 lb final RQ; 45.4 kg final RQ

Ethyl benzene (100-41-4)

CERCLA: 1000 lb final RQ; 454 kg final RQ

Phenol (108-95-2)

CERCLA: 1000 lb final RQ; 454 kg final RQ

TOXIC SUBSTANCES CONTROL ACT (TSCA): All components are on the U.S. EPA TSCA Inventory List.

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Methylisobutyl ketone	108-10-1	Yes	DSL	EINECS
Xylenes (o-, m-, p- isomers)	1330-20-7	Yes	DSL	EINECS
Ethyl benzene	100-41-4	Yes	DSL	EINECS
Phenol	108-95-2	Yes	DSL	EINECS

STATE RIGHT-TO-KNOW:

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Methylisobutyl ketone	108-10-1	Yes	Yes	Yes	Yes	Yes	Yes
Xylenes (o-, m-, p- isomers)	1330-20-7	Yes	Yes	Yes	Yes	Yes	Yes
Ethyl benzene	100-41-4	Yes	Yes	Yes	Yes	Yes	Yes
Phenol	108-95-2	Yes	Yes	Yes	Yes	Yes	Yes

This product is not a consumer product. This product may not be legally authorized for consumer use or sale in a state that has adopted the OTC Model Rule, or in California pursuant to the Consumer Products Regulation of the California Air Resources Board, or in states with similar laws. Please check federal, state and local air control laws for guidance.

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer.

CANADIAN REGULATIONS

This product is regulated under the Canadian Controlled Products Regulations.

WHMIS INFORMATION:

WHMIS Classification:

B2- Flammable liquid

D2A- Chronic effects

D2B- Irritating to skin and eyes



Material Safety Data Sheet

Product No.525 2949; 525 2956; 525 2963

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Methylisobutyl ketone	108-10-1	1 %
Ethyl benzene	100-41-4	0.1 %

EUROPE:

Component Analysis

Component (CAS#)	EC #
Methylisobutyl ketone (108-10-1)	203-550-1
Xylenes (o-, m-, p- isomers) (1330-20-7)	215-535-7
Ethyl benzene (100-41-4)	202-849-4
Phenol (108-95-2)	203-632-7

16. OTHER INFORMATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATINGS:

NFPA Ratings: Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
800-424-9300

FOR ANY OTHER INFORMATION:

REMA TIP TOP/NO. AMERICA
119 Rockland Ave.
NORTHVALE, NJ 07647
201-768-8100

NOTICE: REMA TIP/TOP USA believes that the information contained on this material safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.