



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: ER-42 Hardener

Chemical Family: Ester & Aromatic Hydrocarbons Solution

Product Use: Adhesive/Cement Hardener

Restrictions on Use: Use as directed by manufacturer

Manufacturer: Rema Tip Top - North America
119 Rockland Ave.
Northvale, NJ 07647
Phone: 201 256-8200

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. HAZARD IDENTIFICATION

GHS Classifications

Health Hazards

Acute Toxicity, Inhalation, Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2A
Respiratory Sensitization, Category 1A
Skin Sensitization, Category 1A
Carcinogenicity, Category 2
Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Central Nervous System [Inhalation]
Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Respiratory Tract [Inhalation]
Specific Target Organ Systemic Toxicity, Repeated Exposure, Category 2, Blood [Inhalation, Skin absorption, Ingestion]

Physical Hazards

Flammable Liquid, Category 2

GHS-Labeling

Pictograms:



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015



Signal Word: Danger!

Hazard Statements

- H225: Highly flammable liquid and vapour
- H315: Causes skin irritation
- H317: May cause an allergic skin reaction
- H319: Causes serious eye irritation
- H332: Harmful if inhaled
- H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335: May cause respiratory irritation
- H336: May cause drowsiness or dizziness
- H351: Suspected of causing cancer
- H373: May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- P233: Keep container tightly closed.
- P235: Keep cool.
- P240: Ground/bond container and receiving equipment.
- P241: Use explosion-proof electrical/ventilating/lighting/equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P260: Do not breathe vapours.
- P261: Avoid breathing vapours.
- P264: Wash skin and exposed areas thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P271: Use only outdoors or in a well-ventilated area.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P281: Use personal protective equipment as required.
- P285: In case of inadequate ventilation, wear respiratory protection.

Response:

- P302 + P352: IF ON SKIN: Wash with plenty of soap and water.



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P341: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313: IF exposed or concerned: Get medical advice/attention.
P309 + P311: IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
P314: Get medical advice/attention if you feel unwell.
P321: Specific treatment found in supplemental First Aid section of this SDS (Section 4).
P332 + P313: If skin irritation occurs: Get medical advice/attention.
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313: If eye irritation persists: Get medical advice/attention.
P342 + P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P370 + P378: In case of fire: Use alcohol-resistant foam, carbon dioxide, or dry chemical for extinction.
P362: Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up

Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical characterization

Ester & Aromatic Hydrocarbons Solution

Component*	CAS #	% By Wt.
Ethyl Acetate	141-78-6	65 – 80
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	15 – 25
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	5 – 10
Aromatic polyisocyanate	53317-61-6	5 – 10

*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

4. FIRST AID MEASURES

Inhalation

Symptoms & Effects: Nausea, nose and throat irritation, dizziness, drowsiness, headache



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

Measures: Immediately remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, begin artificial respiration. If breathing is difficult, administer oxygen. Seek immediate medical attention.

Skin Contact

Symptoms & Effects: Slight skin irritation

Measures: Wash skin with plenty of water. Remove contaminated clothing and shoes while washing. Wash contaminated clothing before reuse. If skin irritation persists, seek medical attention.

Eye Contact

Symptoms & Effects: Eye irritation, stinging, tearing, redness, eye swelling

Measures: Immediately rinse eyes with water for at least 15 minutes. Remove contact lenses after the initial few minutes and if easy to do so and resume rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while rinsing. Seek immediate medical attention.

Ingestion

Symptoms & Effects: Stomach or intestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness

Measures: Seek immediate medical attention. Do NOT induce vomiting unless directed to do so by a physician or medical personnel. If the victim is drowsy or unconscious, do not give anything by mouth. Do not give milk. Place individual on their left side and place their head down. Do not leave victim unattended.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Alcohol-resistant foam, Carbon dioxide, Dry chemical, Water spray

Unsuitable Extinguishing Media: Water stream/jet

Hazardous Combustion Products: Hydrogen cyanide (HCN), Isocyanides (NCOs), Nitrogen Oxides (NO_x), Carbon monoxide, Carbon dioxide

Protective Equipment for Fire-Fighters: Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Precautions for Fire-Fighters: Water stream may be ineffective for extinguishment unless used under favorable conditions. This product is volatile and readily gives off flammable vapors which may travel along the ground or be moved by ventilation. Do not allow run-off from firefighting to enter drains or water courses. Use water spray to cool fully closed containers. Avoid spreading burning liquid with water used for cooling purposes.



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Recommended to wear NIOSH approved respiratory apparatus, chemical splash goggles & resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

Personal Precautions: Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

Environmental Precautions: Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike or using oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Methods & Materials for Clean-Up: Immediately evacuate the spilled area and provide maximum ventilation. Only personnel equipped with proper respiratory, eye, and skin protection should be permitted in the area. Contain spilled material with inert, non-combustible absorbent materials such as sand, earth, diatomaceous earth, or vermiculite. Transfer to a suitable container for disposal according to proper federal, state, and local regulations. Notify the proper response units and agencies for any uncontained releases or spills.

7. HANDLING AND STORAGE

Handling: Containers of this material may be hazardous when emptied. Since emptied containers still contain product residues (vapor, liquid, or solid), all hazard precautions given in this SDS must be observed. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Avoid breathing vapors or mists of this product. Avoid eye and skin contact with this material. Skin and eye PPE should be worn at all times when handling this product. When adequate ventilation is not provided, respiratory PPE should also be used. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Do not eat, drink or smoke when using this product.

Storage: Store in a cool, dry, ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up. Keep away from food, drink, and animal foodstuffs.

Incompatible Materials: Amines, Alcohols, Acids, Bases, Strong oxidizing agents, Water



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits :

Exposure limits have not been established for this product.

Ethyl Acetate

CAS # 141-78-6

OSHA	Permissible Exposure Limit (PEL)	400 ppm (1,400 mg/m ³)
ACGIH	Time Weighted Average (TWA)	400 ppm (1,400 mg/m ³)
NIOSH	Recommended Exposure Limit (REL)	400 ppm (1,400 mg/m ³)

Diphenylmethane-4,4'- di-isocyanate (MDI)

CAS # 101-68-8

OSHA	Permissible Exposure Limit (PEL)	0.02 ppm (0.2 mg/m ³)
ACGIH	Time Weighted Average (TWA)	0.005 ppm (0.05 mg/m ³)
NIOSH	Recommended Exposure Limit (REL)	0.005 ppm (0.05 mg/m ³)

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. Provide readily accessible eye wash stations and safety showers.

Occupational Exposure Controls: Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Protective and Hygiene measures: Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

Eye Protection: Recommended to wear tight fitting, chemical splash goggles when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

Hand Protection: Recommended to wear suitable resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Suitable gloves will be based on product use and the period of use, and may include neoprene, butyl-rubber, nitrile rubber, etc.

Skin Protection: Recommended to wear impervious clothing as well as long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances where airborne concentrations are expected to exceed



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow Liquid

Odor: Ester-like

Odor Threshold: No data available

pH: No data available

Melting/Freezing point: No data available

Boiling Point/ Range: 170°F (77°C)

Flash point (Tag closed cup): 25°F (-4°C)

Evaporation rate: No data available

Flammability: Lower Limit: 2.1% (V) **Upper Limit:** 11.5% (V)

Vapor pressure: 90.7 hPa @ 68°F (20°C)

Relative vapor density: No data available

Density: 0.968 g/cm³ (8.07 lbs/gal) @ 68°F (20°C)

Solubility in water: Insoluble

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Ignition temperature: 360°F (180°C)

Decomposition temperature: No data available

Viscosity (dynamic): No data available

10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Product will not undergo hazardous polymerization or other hazardous reactions if storage and use directions are followed.

Conditions to Avoid: Elevated temperatures, Ignition sources, Incompatible materials (see below)

Incompatible Materials: Amines, Alcohols, Acids, Bases, Strong oxidizing agents, Water

Hazardous decomposition products: Hydrogen cyanide (HCN), Isocyanides (NCOs), Nitrogen Oxides (NO_x), Carbon monoxide, Carbon dioxide



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation, Skin contact, Eye contact, Ingestion

Symptoms Related to Physical, Chemical and Toxicological Characteristics: Nausea, nose and throat irritation, dizziness, drowsiness, headache, slight skin irritation, eye irritation, stinging, tearing, redness, eye swelling, stomach or intestinal irritation, vomiting, diarrhea

Delayed and Immediate Effects & Chronic Effects from Exposure: This substance may lead to central nervous system depression and effects such as drowsiness or dizziness. This substance may lead to respiratory tract irritation. This substance may cause an allergic skin reaction. This substance is suspected of causing cancer. With repeated exposure, the substance may have toxic effects on the blood.

Measures of Toxicity:

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: LD₅₀ Rat: > 4,200 mg/kg

Acute Dermal Toxicity: LD₅₀ Rabbit: > 2,000 mg/kg

Acute Inhalation Toxicity: No sufficient data available

Ethyl Acetate

Acute Oral Toxicity

Acute Dermal Toxicity

Acute Inhalation Toxicity

CAS # 141-78-6

LD₅₀ Rat: 5,620 mg/kg

LD₅₀ Rabbit: > 180,000 mg/kg

LC₅₀ Rat: 16,000 mg/l (6 h)

Isocyanic Acid,

Polymethylenepolyphenylene

Ester

Acute Inhalation Toxicity

CAS # 9016-87-9

LC₅₀ Rat: 0.49 mg/l

Diphenylmethane-4,4'-di-isocyanate

Acute Oral Toxicity

CAS # 101-68-8

LD₅₀ Rat: 4,700 mg/kg

Carcinogen Claims:

OSHA: **Yes; 2**

International Agency for Research on Cancer (IARC): **None**

ACGIH: **None**

National Toxicology Program (NTP) Report on Carcinogens: **None**

12. ECOLOGICAL INFORMATION

Eco-toxicity: This substance is not expected to be harmful to aquatic organisms; however it is still strongly advised that this substance does not enter the environment.



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

Ethyl Acetate **CAS # 141-78-6**
Toxicity to Fish LC₅₀ – 220 mg/l (Fathead Minnow; 96 h)
Toxicity to Fish LC₅₀ – 350 mg/l (Rainbow Trout; 96 h)
Toxicity to Daphnia LC₅₀ – 154 mg/l (Water Flea; 48 h)
Toxicity to Algae EC₅₀ – 4,300 mg/l (Algae; 24 h)

Diphenylmethane-4,4'-di-isocyanate **CAS # 101-68-8**
Toxicity to Daphnia EC₅₀ – 0.35 mg/l (Water Flea; 24 h)

Persistence & Degradability: No data available
Bio-accumulative Potential: No data available
Mobility in Soil: No data available
Other Adverse Effects: No data available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.
Contaminated packaging should be emptied as far as possible before disposal.

14. TRANSPORT INFORMATION

DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1133
PROPER SHIPPING NAME: Adhesives, containing a flammable liquid (Ethyl Acetate)
TRANSPORTATION HAZARD CLASS: 3
PACKING GROUP: II
HAZARD LABEL: 3

IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 3
UN NUMBER: UN1133
IMDG PACKING GROUP: II
HAZARD LABEL: 3

Description of the goods

ADHESIVES, CONTAINING A FLAMMABLE LIQUID (ETHYL ACETATE)

IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 3
UN NUMBER: UN1133
HAZARD LABEL: 3

Description of the goods

Adhesives, containing a flammable liquid (Ethyl Acetate)



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

SARA Title III

Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

None Listed

Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Component	CAS #	Weight %	CERCLA RQ
Ethyl Acetate	141-78-6	65 – 80	5,000
Polymeric diphenylmethane diisocyanate	9016-87-9	15 – 25	
MDI	101-68-8	5 – 10	5,000

OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements.

Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

CANADIAN REGULATIONS

WHMIS Classification: B2, D2A, D2B (Based on components)

STATE REGULATIONS

California Proposition 65

This product does not contain chemicals known to the state of California to cause cancer, birth defects or reproductive harm.

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List

Delaware Air Quality Management List

Idaho Air Pollutants List

Illinois Toxic Air Contaminants List

Maine Hazardous Air Pollutants List

Massachusetts Hazardous Substances List

Michigan Critical Materials List

Minnesota Hazardous Substances List



Safety Data Sheet

REMA TIP TOP

Product #: ER42/15G, ER42/30G

SDS #: RTT-IND-033

Rev. # 2

Rev. Date: 7/29/2015

New Jersey RTK Hazardous Substances List
New Jersey TCPA Extremely Hazardous Substances List
New York List of Hazardous Substances
North Carolina Toxic Air Contaminants List
Pennsylvania Hazardous Substances List
Washington Permissible Exposure Air Contaminants List
West Virginia Air Toxic Pollutants List
Wisconsin Hazardous Air Contaminants List

Note: Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
800-424-9300

FOR ANY OTHER INFORMATION:

REMA TIP TOP - NORTH AMERICA
119 Rockland Ave.
NORTHVALE, NJ 07647
201-256-8200

NOTICE: REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.

Date of Issue/Revision: July 29, 2015