



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Name: Tip Top Cement TC 6000

Product Use: Adhesive

Manufacturer: REMA TIP TOP/NO. AMERICA, 119 Rockland Avenue, Northvale, NJ 07647

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)

International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. PRODUCT INGREDIENTS

<u>CHEMICAL NAME:</u>	<u>CAS NUMBER:</u>	<u>% RANGE:</u>	<u>OSHA PEL:</u>
Toluene	108-88-3	25-35	200 ppm TWA
Ethylacetate	141-78-6	25-35	400 ppm TWA; 1400 mg/m ³ TWA
Xylenes (o-, m-, p- isomers)	1330-20-7	10-20	100 ppm TWA; 435 mg/m ³ TWA
Lead tetraoxide	1314-41-6	0.1-0.5	Not Established

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Lead, inorganic compounds.

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

This product is regulated under the Canadian Controlled Products Regulations.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

This product is a brown liquid with an aromatic odor. This product is a flammable liquid and vapor. Vapors may cause flash fire. It can cause eye, skin, respiratory and digestive system irritation. Repeated exposure may cause skin dryness or cracking. Harmful by inhalation and in contact with skin. Aspiration hazard. Symptoms of exposure may include central nervous system depression. Components are known to cause carcinogenic, teratogenic and neurological effects. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EYE: This product may cause irritation to the eyes. Symptoms may include stinging, tearing, redness, swelling, and eye damage.

SKIN: This product is irritating to the skin. Prolonged and/or repeated skin contact with this product may cause irritation, defatting of skin and dermatitis. Components can be absorbed through skin in harmful amounts.

INGESTION: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. May produce central nervous system depression. If aspirated (liquid enters the lung), the product may be rapidly absorbed through the lungs and can result in chemical pneumonitis and pulmonary edema/hemorrhage.



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

INHALATION: This product may be harmful by inhalation. Symptoms may include irritation, nausea, vomiting, headache, difficulty breathing, drowsiness, dizziness, loss of coordination, kidney damage, liver damage, unconsciousness, and coma.

4. FIRST AID

EYES: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. If irritation persists get medical attention.

SKIN: For skin contact flush with large amounts of water while removing contaminated clothing. If irritation persists, get medical attention. Wash contaminated clothing before reuse.

INGESTION: Do not induce vomiting. Call a physician immediately. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

INHALATION: Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration. Seek medical attention.

NOTE TO PHYSICIAN: Provide general supportive measures and treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point: -5°C (23°F)

Upper Flammable Limit (UFL): Not Available

Auto Ignition: >430°C (>806°F)

Method Used: Not Available

Lower Flammable Limit (LFL): 1.2%

Flammability Classification: Class IB

HAZARDOUS COMBUSTION PRODUCTS: Upon decomposition, this product emits oxides of sulfur, oxides of nitrogen, hydrogen chloride, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical, water fog or fine spray.

FIRE FIGHTING INSTRUCTIONS: DANGER, FLAMMABLE! Clear fire area of unprotected personnel and isolate. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.

PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS: Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

6. ACCIDENTAL RELEASE MEASURES

CONTAINMENT PROCEDURES: Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Handling equipment must be grounded to prevent sparking. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

CLEAN-UP PROCEDURES: Wear appropriate personal protective equipment. Eliminate ignition sources including sources of electrical, static or frictional sparks. Ventilate the contaminated area. Absorb spill with inert material. Shovel



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

material into properly labeled closed metal containers for disposal. Use non-sparking tools. Place in non-leaking containers for immediate disposal. Flush area with water to remove trace residue. Do not allow the spilled product to enter public drainage system or open water courses.

EVACUATION PROCEDURES: Persons not wearing appropriate protective equipment should be excluded from area of spill until clean up has been completed.

SPECIAL PROCEDURES: Follow all Local, State, Federal and Provincial regulations for disposal. Notify the proper authorities if entry to the environment occurs.

7. HANDLING & STORAGE

HANDLING: Keep liquid and vapor away from heat, sparks and flames. Surfaces that are sufficiently hot may ignite liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash fire can result. Keep containers closed when not in use. Use with adequate ventilation.

Containers, even those that have been emptied, can contain explosive vapors. DO NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT pressurize drum containers to empty them.

Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment.

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Air-dry contaminated clothing in a well ventilated area before laundering.

STORAGE: Keep packaged in original, labeled containers until use. Store in a cool, dry, well-ventilated area. Store this product in air-tight containers away from sources of heat and light. Ground all equipment to prevent accumulation of static charge. Store away from incompatible materials. Do not remove or deface label. Do not reuse container without recycling or reconditioning in accordance with any Federal, Provincial, State or local laws. Do not use cutting or welding torches, open flames, or electric arcs on empty or full containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION: Wear safety glasses. Chemical goggles and/ or face shields should be worn, when splashing is a possibility. Contact lenses should not be exposed. If vapor exposure causes eye discomfort, use a full-face respirator.

SKIN PROTECTION: Use impervious gloves. Use of impervious apron and boots are recommended. Wash contaminated clothing before reuse.

RESPIRATORY PROTECTION: If recommended exposure limits are exceeded, a NIOSH approved, continuous flow supplied air-respirator, hood or helmet is acceptable.



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

EXPOSURE GUIDELINE(s):

Component Exposure Limits

REMA TIP/TOP USA recommends that its customers minimize employee exposure. REMA therefore suggests that its customers consider adopting the lower of the current OSHA PEL or the ACGIH TLV's for the purpose of evaluating employee exposures. The TLV's recommended by the ACGIH have been updated on a continuing basis.

Toluene (108-88-3)

ACGIH: 50 ppm TWA
Skin - potential significant contribution to overall exposure by the cutaneous route
OSHA: 200 ppm TWA
300 ppm Ceiling
NIOSH: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL

Ethylacetate (141-78-6)

ACGIH: 400 ppm TWA
OSHA: 400 ppm TWA; 1400 mg/m³ TWA
NIOSH: 400 ppm TWA; 1400 mg/m³ TWA

Xylenes (o-, m-, p- isomers) (1330-20-7)

ACGIH: 100 ppm TWA
150 ppm STEL
OSHA: 100 ppm TWA; 435 mg/m³ TWA

Lead tetraoxide (1314-41-6)

ACGIH: 0.05 mg/m³ TWA (as Pb) (related to Lead, inorganic compounds)
OSHA: 50 µg/m³ TWA (as Pb); 30 µg/m³ Action Level (as Pb. Poison - see 29 CFR 1910.1025) (related to Lead, inorganic compounds)

Component Exposure Limits – Canada

The following Provincial Exposure Limits apply for this product's components.

Toluene (108-88-3)

Alberta: 50 ppm TWA; 188 mg/m³ TWA
British Columbia: 50 ppm TWA
Manitoba: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL
New Brunswick: 50 ppm TWA; 188 mg/m³ TWA
NW Territories: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL
Nova Scotia: 50 ppm TWA
Nunavut: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL
Ontario: 50 ppm TWAEV
Quebec: 100 ppm TWAEV; 377 mg/m³ TWAEV
150 ppm STEV; 565 mg/m³ STEV
Saskatchewan: 188 mg/m³ TWA; 50 ppm TWA
235 mg/m³ STEL; 60 ppm STEL
Yukon: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

Ethylacetate (141-78-6)

Alberta:	400 ppm TWA; 1440 mg/m ³ TWA
British Columbia:	150 ppm TWA
Manitoba:	400 ppm TWA; 1400 mg/m ³ TWA
New Brunswick:	400 ppm TWA; 1440 mg/m ³ TWA
NW Territories:	400 ppm TWA; 1441 mg/m ³ TWA 500 ppm STEL; 1801 mg/m ³ STEL
Nova Scotia:	400 ppm TWA
Nunavut:	400 ppm TWA; 1441 mg/m ³ TWA 500 ppm STEL; 1801 mg/m ³ STEL
Ontario:	400 ppm TWAEV; 1440 mg/m ³ TWAEV
Quebec:	400 ppm TWAEV; 1400 mg/m ³ TWAEV
Saskatchewan:	1440 mg/m ³ TWA; 400 ppm TWA 1800 mg/m ³ STEL; 500 ppm STEL
Yukon:	400 ppm TWA; 1400 mg/m ³ TWA 400 ppm STEL; 1400 mg/m ³ STEL

Xylenes (o-, m-, p- isomers) (1330-20-7)

Alberta:	100 ppm TWA; 434 mg/m ³ TWA 150 ppm STEL; 651 mg/m ³ STEL
British Columbia:	100 ppm TWA 150 ppm STEL
Manitoba:	100 ppm TWA; 435 mg/m ³ TWA 150 ppm STEL; 655 mg/m ³ STEL
New Brunswick:	100 ppm TWA; 434 mg/m ³ TWA 150 ppm STEL; 651 mg/m ³ STEL
NW Territories:	100 ppm TWA; 434 mg/m ³ TWA 150 ppm STEL; 652 mg/m ³ STEL
Nova Scotia:	100 ppm TWA 150 ppm STEL
Nunavut:	100 ppm TWA; 434 mg/m ³ TWA 150 ppm STEL; 652 mg/m ³ STEL
Ontario:	100 ppm TWAEV; 435 mg/m ³ TWAEV 150 ppm STEV; 650 mg/m ³ STEV
Quebec:	100 ppm TWAEV; 434 mg/m ³ TWAEV 150 ppm STEV; 651 mg/m ³ STEV
Saskatchewan:	434 mg/m ³ TWA; 100 ppm TWA 651 mg/m ³ STEL; 150 ppm STEL
Yukon:	100 ppm TWA; 435 mg/m ³ TWA 150 ppm STEL; 650 mg/m ³ STEL

Lead tetraoxide (1314-41-6)

Alberta:	0.05 mg/m ³ TWA (as Pb) (related to Lead, inorganic compounds)
British Columbia:	0.05 mg/m ³ TWA (as Pb) (related to Lead inorganic compounds)
Manitoba:	0.15 mg/m ³ TWA (as Pb, dust and fume) (related to Lead, inorganic compounds)
New Brunswick:	0.05 mg/m ³ TWA (as Pb) (related to Lead, inorganic compounds)
NW Territories:	0.15 mg/m ³ TWA (dust and fume, as Pb) (related to Lead, inorganic) 0.45 mg/m ³ STEL (dust and fume, as Pb) (related to Lead, inorganic)
Nova Scotia:	0.05 mg/m ³ TWA (as Pb) (related to Lead, inorganic compounds)
Nunavut:	0.15 mg/m ³ TWA (dust and fume) (related to Lead, inorganic)



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

	0.45 mg/m ³ STEL (dust and fume) (related to Lead, inorganic)
Ontario:	0.05 mg/m ³ TWAEV (designated substance regulation) (related to Lead, inorganic compounds)
Quebec:	0.15 mg/m ³ TWAEV (dust and fume, as Pb) (related to Lead inorganic compounds)
Saskatchewan:	0.15 mg/m ³ TWA (dust and fume, as Pb) (related to Lead inorganic compounds) 0.45 mg/m ³ STEL (dust and fume, as Pb) (related to Lead inorganic compounds)
Yukon:	0.15 mg/m ³ TWA (dust and fume, as Pb) (related to Lead, inorganic) 0.45 mg/m ³ STEL (dust and fume, as Pb) (related to Lead, inorganic)

9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE: Brown liquid

ODOR: Aromatic

ODOR THRESHOLD: Not Available

BOILING POINT: >76°C (>168.8°F)

SOLUBILITY IN WATER: Insoluble

SPECIFIC GRAVITY: 0.91 g/ml

VAPOR PRESSURE: 97 hPa

% VOLATILE: <85%

10. STABILITY & REACTIVITY

INCOMPATIBILITY WITH OTHER MATERIALS: Materials to avoid are oxidizing materials, combustible materials, acids, amines and bases.

HAZARDOUS POLYMERIZATION: Will not occur.

DECOMPOSITION PRODUCTS: Upon decomposition, this product emits oxides of sulfur, oxides of nitrogen, hydrogen chloride, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Through inhalation, ingestion or passage of the material through the skin the following symptoms may occur: stomach or intestinal upset (nausea, vomiting, diarrhea); irritation (nose, throat, airway); central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness); temporary changes in mood and behavior; loss of appetite; loss of coordination; irregular heartbeat; narcosis (dazed or sluggish feeling). Components may be absorbed through the skin.

Lead has a wide variety of reproductive effects in humans. It can affect both the male and female reproductive organs as well as egg and sperm production and development. Lead can also cause neurodevelopmental debilitations in children from both prenatal and postnatal exposures. Inorganic lead has been found to have toxic effects on both the central and peripheral nervous systems. Symptoms of lead toxicity include behavioral disturbances such as irritability, restlessness,



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

insomnia, and other sleep disturbances, fatigue, vertigo, headache, poor memory, tremor, depression, and apathy. With more severe exposure, symptoms can progress to drowsiness, stupor, hallucinations, delirium, convulsions, and coma.

CHRONIC TOXICITY

Liver and kidney damage may occur. Repeated or prolonged contact has a defatting action, causing drying, redness, dermatitis. Exposure to toluene may affect the developing fetus.

CARCINOGENICITY

Component Carcinogenicity

Toluene (108-88-3)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71, 1999; Monograph 47, 1989 (Group 3 (not classifiable))

Xylenes (o-, m-, p- isomers) (1330-20-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71, 1999; Monograph 47, 1989 (Group 3 (not classifiable))

Lead tetraoxide (1314-41-6)

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans (related to Lead, inorganic compounds)

OSHA: 50 µg/m³ TWA (as Pb); 30 µg/m³ Action Level (as Pb. Poison - see 29 CFR 1910.1025) (related to Lead, inorganic compounds)

IARC: Monograph 87, in preparation (related to Lead, inorganic compounds) (Group 2A (probably carcinogenic to humans))

12. ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Toluene (108-88-3)

Test & Species

Test & Species	Concentration	Conditions
96 Hr LC50 Pimephales promelas	25 mg/L [flow-through]	1 day old
96 Hr LC50 Oncorhynchus mykiss	24.0 mg/L [static]	
96 Hr LC50 Lepomis macrochirus	24.0 mg/L [static]	
96 Hr LC50 Lepomis macrochirus	13 mg/L [static]	
96 Hr EC50 Selenastrum capricornutum	>433 mg/L	
30 min EC50 Photobacterium phosphoreum	19.7 mg/L	
48 Hr EC50 water flea	11.3 mg/L	
48 Hr EC50 water flea	310 mg/L	
48 Hr EC50 Daphnia magna	11.3 mg/L	



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

Ethylacetate (141-78-6)

Test & Species

96 Hr LC50 Pimephales promelas	230 mg/L [flow-through]
96 Hr LC50 Oncorhynchus mykiss	484 mg/L [flow-through]
48 Hr EC50 Scenedesmus subspicatus	3300 mg/L
5 min EC50 Photobacterium phosphoreum	1180 mg/L
15 min EC50 Photobacterium phosphoreum	5870 mg/L
2 Hr EC50 Pseudomonas fluorescens	7400 mg/L
15 min EC50 Pseudomonas fluorescens	1500 mg/L
48 Hr EC50 Daphnia magna	717 mg/L

Conditions

Xylenes (o-, m-, p- isomers) (1330-20-7)

Test & Species

96 Hr LC50 Pimephales promelas	13.4 mg/L [flow-through]
96 Hr LC50 Oncorhynchus mykiss	8.05 mg/L [flow-through]
96 Hr LC50 Lepomis macrochirus	16.1 mg/L [flow-through]
96 Hr LC50 Pimephales promelas	26.7 mg/L [static]
24 hr EC50 Photobacterium phosphoreum	0.0084 mg/L
48 Hr EC50 water flea	3.82 mg/L
48 Hr LC50 Gammarus lacustris	0.6 mg/L

Conditions

Lead tetraoxide (1314-41-6)

Test & Species

96 Hr LC50 Gambusia affinis	>56000 mg/L [static]
-----------------------------	----------------------

Conditions

13. DISPOSAL CONSIDERATIONS

DISPOSAL: Waste must be handled in accordance with all federal, state, provincial, and local regulations.

UNUSED & UNCONTAMINATED PRODUCT:

Component Waste Numbers

Toluene (108-88-3)

RCRA: waste number U220

Ethylacetate (141-78-6)

RCRA: waste number U112 (Ignitable waste)

Xylenes (o-, m-, p- isomers) (1330-20-7)

RCRA: waste number U239 (Ignitable waste, Toxic waste)

If discarded, this product is considered a RCRA ignitable waste, D001.



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

14. TRANSPORT INFORMATION

US DOT Information

Shipping Name: Adhesives

UN/NA #: UN1133 Hazard Class: 3 Packing Group: III

Required Label(s): FLAMMABLE LIQUID

Additional Info.: PLACARD (WHEN REQUIRED): FLAMMABLE LIQUID, 3

EXCEPTIONS: DOT Paragraphs 173.150, 173.202, & 173.242.

ALTERNATE SHIPPING ARRANGEMENTS: Based on package or shipping container size, this product may be shipped as a, "Limited Quantity", and reclassified as, "ORM-D" Material.

TDG Information

Shipping Name: Adhesives

UN/NA #: UN1133 Hazard Class: 3 Packing Group: III

Required Label(s): FLAMMABLE LIQUID

IMDG Information

Additional Info.:F-E, S-D

IATA Information

Additional Info.: 3

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

SARA 313 INFORMATION:

Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 313 (40 CFR 372.65).

Toluene (108-88-3)

SARA 313: 1.0 % de minimis concentration

Xylenes (o-, m-, p- isomers) (1330-20-7)

SARA 313: 1.0 % de minimis concentration

Lead tetraoxide (1314-41-6)

SARA 313: 0.1 % Supplier notification limit (Chemical Category N420) (related to Inorganic lead compounds)

SARA HAZARD CATEGORY:

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactive: No



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA):

Component Analysis

This material contains one or more of the following chemicals required to be identified under CERCLA (40 CFR 302.4).

Toluene (108-88-3)

CERCLA: 1000 lb final RQ; 454 kg final RQ

Ethylacetate (141-78-6)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Xylenes (o-, m-, p- isomers) (1330-20-7)

CERCLA: 100 lb final RQ; 45.4 kg final RQ

TOXIC SUBSTANCES CONTROL ACT (TSCA): All components are on the U.S. EPA TSCA Inventory List.

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Toluene	108-88-3	Yes	DSL	EINECS
Ethylacetate	141-78-6	Yes	DSL	EINECS
Xylenes (o-, m-, p- isomers)	1330-20-7	Yes	DSL	EINECS
Lead tetraoxide	1314-41-6	Yes	DSL	EINECS

STATE RIGHT-TO-KNOW:

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes	Yes
Ethylacetate	141-78-6	Yes	Yes	Yes	Yes	Yes	Yes
Xylenes (o-, m-, p- isomers)	1330-20-7	Yes	Yes	Yes	Yes	Yes	Yes
Lead tetraoxide (related to Lead, inorganic)	1314-41-6	No	Yes	Yes ¹	No	No	No

This product is not a consumer product. This product may not be legally authorized for consumer use or sale in a state that has adopted the OTC Model Rule, or in California pursuant to the Consumer Products Regulation of the California Air Resources Board, or in states with similar laws. Please check federal, state and local air control laws for guidance.

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

CANADIAN REGULATIONS

This product is regulated under the Canadian Controlled Products Regulations.

WHMIS INFORMATION:

WHMIS Classification:

B2- Flammable Liquid

D1A- Very Toxic Substance at >1%

D2A- Chronic effects

D2B- Irritating to eyes and skin



Material Safety Data Sheet

REMA TIP TOP

Product #'s:5252262

MSDS #: RTT-IND-037

Rev. # 1

Rev. Date: 2/19/2008

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Toluene	108-88-3	1 %
Ethylacetate	141-78-6	1 %

EUROPE:

Component Analysis

Component (CAS#)	EC #
Toluene (108-88-3)	203-625-9
Ethylacetate (141-78-6)	205-500-4
Xylenes (o-, m-, p- isomers) (1330-20-7)	215-535-7
Lead tetraoxide (1314-41-6)	215-235-6

16. OTHER INFORMATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATINGS:

NFPA Ratings: Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
800-424-9300

FOR ANY OTHER INFORMATION:

REMA TIP TOP/NO. AMERICA
119 Rockland Ave.
NORTHVALE, NJ 07647
201-768-8100

NOTICE: REMA TIP/TOP USA believes that the information contained on this material safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.