

## RAD 100 Series Section Repair Chart / OTR

Series 100	Series 75-80	Series 65	①		RAD No.	②		②		③			
			max. A mm	max. R mm		max. A inch	max. R inch	max. C Ø mm	max. A x R mm	max. C Ø inch	max. A x R inch	max. S mm	max. S inch
14.00-30.00	15.5-33.5	20/-50/	20	70	¾	2¾	144	20	20 x 40	¾	¾ x 1½	15	⅝
			25	150	1	6	146	40	40 x 60	1⅝	1⅝ x 2¾	20	¾
			50	100	2	4							
16.00-40.00	17.5-55	25/-65/	25	250	1	10	150	50	50 x 80	2	2 x 3¼	35	1⅞
			50	150	2	6							
			50	250	2	10	152	90	90 x 120	3½	3½ x 4¾	55	2⅛
			100	150	4	6							
18.00-40.00	20.5-55	35/-65/	50	300	2	12	156	90	90 x 140	3½	3½ x 5½	60	2⅜
			100	200	4	8							
			130	180	5¼	7⅞	168	100	100 x 150	4	4 x 6	70	2¾
			140	170	5½	6¾							
27.00-40.00	29.5-55	45/-65/	60	400	2⅜	16	160	90	90 x 180	3½	3½ x 7⅞	65	2½
			120	250	4¾	10							
33.00-40.00	37.25-55	55/-65/	60	480	2⅜	18⅞	162	100	100 x 220	4	4 x 8⅝	70	2¾
			120	250	4¾	10							
14.00-18.00	15.5-20.5	20/-35/	-	-	-	-	145	40	40 x 70	1⅝	1⅝ x 2¾	-	-
21.00-30.00	23.5-33.5	40/-50/	-	-	-	-		25	25 x 50	1	1 x 2	-	-
16.00-21.00	17.5-23.5	25/-35/	-	-	-	-		60	60 x 90	2⅜	2⅜ x 3½	-	-
24.00-30.00	26.5-33.5	40/-50/	-	-	-	-	155	40	40 x 70	1⅝	1⅝ x 2¾	-	-
33.00-40.00	37.25-50.5	55/-65/	-	-	-	-		25	25 x 50	1	1 x 2	-	-
21.00-30.00	23.5-33.5	40/-50/	-	-	-	-	165	80	80 x 110	3¼	3¼ x 4¾	-	-
33.00-40.00	37.25-55	55/-65/	-	-	-	-		60	60 x 90	2⅜	2⅜ x 3½	-	-
27.00-40.00	29.5-55	45/-65/	-	-	-	-	175	100	100 x 140	4	4 x 5½	-	-
24.00-	26.5-	40/-	-	-	-	-	185	150	150 x 220	6	6 x 8⅝	-	-
36.00-	36.5-	40/-	-	-	-	-	185+	300	100 x 140	12	4 x 5½	-	-

This is the repair chart valid at the time of printing.  
Always refer to the repair chart and safety advice packed with the product!

