



Technical Data Sheet

REMA TIP TOP BEAD SEALER (Flammable)

TDS #: RTTNA – 009

Rev. # 1

Rev. Date: 4/3/2009

PART NUMBERS: 960F

CONTAINERS/PACKAGING: 32 fl. oz. Can

FIELD OF APPLICATION: RTT Bead Sealer is specially formulated to seal small leaks at the rim and bead area of the tire at time of mounting. It is suitable for use with radial and bias construction tires. It is NOT intended as replacement for tire mounting demounting lubricants.

NOTE: Not to be used on tires that have suffered bead damage!

PRODUCT ADVANTAGES: Easy “brush on” application.
Fast drying.
Long shelf life.

INSTRUCTIONS FOR USE: After the tire has been demounted, check for any damage that may render the tire unusable. Using a clean brush, apply a thick coat of Rema Tip Top Bead Sealer to the bead seat area of the wheel. Mount the tire on the wheel and inflate to recommended air pressure. Check for leaks. Allow the tire to sit for about 15 minutes and recheck for leaks. Close container tightly after use.

NOTE: Solvents may cause some discoloration or other cosmetic damage to some wheels. Rema Tip Top advises that a small amount be applied to an inconspicuous area and inspected prior to final use!

SAFETY INSTRUCTIONS: **CAUTION: Highly Flammable!**
Do NOT use Rema Tip Top Bead Sealer as a replacement for any vulcanizing solutions (cements) or Innerliner Sealer. Use in a well ventilated work area. Refer to MSDS and package for more detailed instructions.

SHELF LIFE: Four (4) years in unopened container from date of manufacture

BASE SOLVENT: n-Heptane (refer to MSDS for detailed data)

RECOMMENDED STORAGE CONDITIONS: Store in a dark, moisture free environment, away from direct



Technical Data Sheet

REMA TIP TOP BEAD SEALER (Flammable)

TDS #: RTTNA – 009

Rev. # 1

Rev. Date: 4/3/2009

sunlight

Keep away from open flames, sparks, and other sources of ignition.

Protect from freezing

Comply with all local, state, and federal regulations

DRYING TIME:

Drying time depends on atmospheric conditions, and may be longer in cold, humid areas

WAIT TIME for RETURNING TIRE TO SERVICE:

Not applicable

ADDITIONAL INFO:

Do not dilute. Use full strength only!

Keep container tightly closed when not in use.

CANADIAN REGULATIONS

WHMIS Classification: B2, D2B

This product is regulated under the Canadian Controlled Products Regulations.

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Heptane (n-)	142-82-5	1 %

NOTICE: REMA TIP TOP / NORTH AMERICA believes that the information contained on this data sheet is accurate. It is based on extensive tests and represents standard values. However, it may not contain information on all confirmed properties. REMA TIP TOP / North America reserves the right to carry out improvements and technical development to this product at its discretion. For detailed application instructions, always refer to the appropriate Rema Tip Top Instruction Manuals and/or Repair Instruction CD's. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.