



// ONE BRAND // ONE SOURCE // ONE SYSTEM



## REMA COMBI-SKIRT

Dual Durometer Skirt Board Rubber *"The Best of Both Worlds".*

## REMA COMBI-SKIRT - Dual Durometer Skirt Board Rubber *"The Best of Both Worlds"*

### LONGER LASTING PERFORMANCE

- This means less maintenance dollars spent on skirt board rubber replacement.

### BETTER IMPACT RESISTANCE

- REMA COMBI-SKIRT was designed to resist heavy impact at loading areas by combining a layer of REMASKIRT 60 on one side to absorb impact, with REMASKIRT 50 to provide excellent sealing properties.
- This truly offers the "Best of Both Worlds" for your skirt rubber needs.

### REDUCED BELT WEAR

- REMA COMBI-SKIRT is designed to provide optimum sealing properties and reduced conveyor belt wear, while also absorbing heavy impact.
- Since REMASKIRT 50 is a softer rubber, compared to conventional skirting, it greatly reduces wear in the top cover of your conveyor belt.

### TECHNICAL DATA

	REMASKIRT 50	REMASKIRT 60	
Color	Orange	Black	
Rubber	NR	BR/IR/SBR	DIN ISO 1629
Hardness	51 Shore A	60 Shore A	DIN ISO 7619-1
Abrasion	160 mm <sup>3</sup>	90 mm <sup>3</sup>	DIN ISO 4649
Density	1.11 g/cm <sup>3</sup> (69.30 lb/ft <sup>3</sup> )	1.13 g/cm <sup>3</sup> (70.54 lb/ft <sup>3</sup> )	DIN EN ISO 1183-1
Tensile Strength	27 N/mm <sup>2</sup> (3916 psi)	18 N/mm <sup>2</sup> (2611 psi)	DIN 53 504
Elongation at break	600%	470 %	DIN 53 504
Resilience	70%	44 %	DIN 53 512
Tear Growth Resistance	15 N/mm (0.097 Lbf/in)	15 N/mm (0.097 Lbf/in)	ISO 34-1 Methode A

### REMA TIP TOP/North America, Inc.

1500 Industrial Blvd. • Madison, GA 30650 • Phone 800.334.REMA (7362) • 706.752.4000 • Fax 706.752.4015 → [www.rematiptop.com](http://www.rematiptop.com)