



// ONE BRAND // ONE SOURCE // ONE SYSTEM

REMALINE 25 - The safe protection against wear and material build-up

REMA TIP TOP's high-quality REMALINE lining offers optimum surface protection for your machinery and equipment while minimizing production downtime, reducing maintenance costs, and increasing productivity.

APPLICATION AREAS

Due to its highly elastic properties, REMALINE 25 is suitable for preventing build-up in equipment conveying sand/water mixtures and fine material. REMALINE 25 also offers excellent noise dampening and reduction of noise emissions.

TYPICAL FIELDS OF USE

- Covers for conveyor rollers
- Lining of elevator and excavator buckets
- Outlet funnels for dry mortar
- Flexilo and bunker lining
- Noise reduction lining
- Cushioning cover for rollers
- Also used as a dust cover

ADVANTAGES

- Build-up elimination
- Noise reduction
- Easy and fast installation
- Increases the efficiency of your equipment
- Technical consultation and data available anytime



TECHNICAL PROPERTIES

Product characteristics	REMALINE 25 is a soft material based on natural rubber with elastic properties. CN bonding layer: REMALINE 25 comes equipped with a CN bonding layer, which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.	
Storage stability	Max. 24 months At 77°F ± 3.6°F with no loss in quality Subject to DIN regulation 7716	
Color		Black
Polymer	DIN ISO 1629	NR/IR
Hardness	DIN ISO 7619-1	33 Shore A
Abrasion	DIN ISO 4649	150(5N) mm ³
Specific Weight	DIN EN ISO 1183-1	0.97 g/cm ³ (60.56 lb/ft ³)
Tensile Strength	DIN 53 504	14 N/mm ²
Elongation at break	DIN 53 504	820%
Resilience Elasticity	DIN 53 512	74%
Tear Growth Resistance	ISO 34-1 Method A	7 N/mm
Available sizes*	Standard thickness	1/8", 1/4", 3/8", 5/8"
	Standard width	60", 78"

*Other sizes available on request.

REMA TIP TOP/North America, Inc.

1500 Industrial Blvd. • Madison, GA 30650 • Phone 800.334.REMA (7362) • 706.752.4000 • Fax 706.752.4015 → www.rematiptop.com