



REMATIP TOP - REMACLEAN CAB

REMACLEAN CAB Green and **REMACLEAN CAB Grey** are three-ply combi scraping rubber (CAB) with a wear resistant outer layer and elastic inner layer.

PRODUCT DESCRIPTION

- Consists of three layers of rubber, two hard rubber outer layers surrounding a soft inner core.
- This combination provides excellent conveyor belt cleaning and can utilize existing scraper devices mounted on the system.
- The dual rubber design provides the best cleaning and abrasion resistance available.
- It routinely outperforms urethane and other rubber compounds for service life and cleaning ability.
- Harder outer layers provide a scraping/cleaning effect, while the softer inner layer bulges out under compression and provides a wiping/cleaning action.

PRODUCT OVERVIEW

- Scraper rubber may protrude from its support up to 1.5 times its thickness
- Excellent wear resistance
- · Very belt friendly
- low friction on conveyor belt
- Production widths up to 78" wide
- Designed for temperature ranges of -40°F to 158°F
- Can be used with V plows and angled plows
- More forgiving to your belt fasteners and vulcanized splices than Urethane scrapers

TYPICAL APPLICATIONS

• Universally applicable as a scraper for granular, slightly sticky and moist material

TECHNICAL DATA

		REMACLEAN CAB Green		REMACLEAN CAB Grey	
		Inner Layer	Outer Layers	Inner Layer	Outer Layers
Polymer Basis	DIN ISO 1629	NR/BR	NR/BR	NR	BR/IR/NR
Specific Weight	DIN EN ISO 1183-1	1.09 g/cm³	1.13 g/cm³	1.10 g/cm³	1.23 g/cm³
Hardness	DIN ISO 7619-1	54 Shore A	70 Shore A	50 Shore A	82 Shore A
Resilience		75%	47%	75%	47%
Color		Black / Green / Black		Black / Grey / Black	

PART NUMBERS

Part Number	Description	Thickness	Length	Width	Weight
CAB/BGB/3/4B	REMACLEAN CAB Green	3/4"	33'	78"	4.88 lbs/ft²
CAB/BGB/1B**	REMACLEAN CAB Green	ן"	33'	78"	6.00 lbs/ft²
CAB/BGB/2A	REMACLEAN CAB Green	2"	16'-6"	78"	11.80 lbs/ft²
	REMACLEAN CAB Grey	ן"	33'	78"	6.27 lbs/ft²

^{*} Additional thicknesses are available as a non-stock item, special order required. Typical lead time of 10-12 weeks.

^{**} Available as full roll or cut piece