



// ONE BRAND // ONE SOURCE // ONE SYSTEM



T-REX

T-REX Skirting

T-REX Skirting

PRODUCT DESCRIPTION

- **T-REX 40 Skirting** is a natural rubber based skirting that provides excellent sealing of conveyed material and outstanding wear life, reducing the cost of maintenance and down time.
- Compared to standard rubber skirting, **T-REX 40 Skirting** can provide up to 2x the wear life.
- **T-REX** is the economical solution for plants that want a longer wear life at a competitive price.

APPLICATION AREAS

- The properties of **T-REX 40 Skirting** make it an excellent value for the sand and gravel industry. It features good resistance to wet, abrasive and sharp particles.
- It also repels sticky substances, reducing material build up.

TYPICAL FIELDS OF USE

- Conveyor system skirting
- Dust suppression
- Loading area containment

ADVANTAGES:

- Longer wear life compared to standard skirting
- Cut and gouge resistance
- Economical pricing
- Available in full roll or cut widths
- 50 foot roll length

TECHNICAL DATA

Color	Red	
Polymer	NR	DIN ISO 1629
Hardness	45 Shore A	DIN ISO 7619-1
Abrasion	110 (5N) mm ³	DIN ISO 4649
Density	1.12 g/cm ³ (69.92 lb/ft ³)	DIN EN ISO 1183-1
Tensile Strength	20 N/mm ² (2900 psi)	DIN 53 504
Elongation at break	650%	DIN 53 504
Resilience	70%	DIN 53 512
Tear Growth Resistance	10N/mm (1450 psi)	ISO 34-1 Methode A

T-REX 40 SKIRTING (RED): PART NUMBERS

Product #	U.S. Part #	Thickness	Length	Width	Weight
101062012	101062012	12 mm / ½"	15.23 m / 50'	2000 mm / 78"	2.70 lb/ft ²
101062018	101062018	18 mm / ¾"	15.23 m / 50'	2000 mm / 78"	4.05 lb/ft ²
101062025	101062025	25 mm / 1"	15.23 m / 50'	2000 mm / 78"	5.40 lb/ft ²