



// ONE BRAND // ONE SOURCE // ONE SYSTEM

TECHNICAL BULLETIN - REMA TIP TOP Product Shelf Life

PRODUCT		RTTNA Specifications			
Product Name	Product Codes	1 Year	2 Years	4 Years	5 years
Pre-Buff Cleaner - Flammable Liquid	71F				X
Pre-Buff Cleaner - Flammable Spray	70F		X		
Special Blue Cement - Flammable	BL-8F, BL-32F		X		
Cold Vulcanizing Fluid - Flammable	203-F, 204-F		X		
Repair Sealant - Flammable	76F		X		
OTR-F Cement - Flammable	OTR-F 700		X		
MTR-F Solution- Flammable	MTR-F 700			X	
Bead Sealer - Flammable	960F		X		
A & B Compound - Flammable	50F, 51F	X			
REMABOND Brush Cement (Flammable)	16 RBB 5G, 16 RBB D	X			
REMABOND Spray Cement (Flammable)	16 RBS 5G, 16 RBS D	X			
BLACK-OUT Ready to Use Black Tire Paint	BLACKOUT-5, BLACKOUT-55		X		
Blue Floater Gum	5570, 5571		X		
MTR Rope Rubber	5567-26.5	X			
MTR Cushion Gum	5561, 5562, 5563	X			
Radial Tire Repairs	All RAD Series				X
Bias Tire Repairs	All PN Series				X
M-RCF 400	All M-RCF Series 400	X			
MINICOMBI	A-3, A-3-R, A-4.5, A-6, A-6-R, B-8MC, B-8-R, B-10, B-10-R				X
Stems	RS-6, RS-8, RS-10, RS-12, RS-22, 193, 194				X
Sealastic Repairs	521, 561, 571, 581			X	
Tread Production Cement	16 TPC 5G, 16 TPC D	X			
Tube Repairs - Red	F0-P, F1-P, 0, 1, 2, 3, 4, 5, 6, 7, 7B				X
Tube Repairs - Black	B-0, B-1, B-2, B-3, B-7, B-7B				X
T2 Compound and Solution	5177300, 5177310, 5177323, 5177330, 5177347, 5177354, 5177402, 5179008, 5179015, 101000069, & 101000070	X			
Universal Repairs	UP-3, UP-4.5, UP-6, UP-6P, UP-8, UP-8P FRU1-MP, FRU1-P, FRU2-MP, FRU2-P				X
Tire Mounting Lubricants Universal Mounting Paste, Tire Mounting Compounds, Black-Ice Stop Rust Rim Release, OTR Tire Mounting/ Packing Compound, Tire Mounting Liquid Lube	75, 75N, 74, 2178, 2180X, 2183, 2014, 2278, 2280, 2282, 2214, 2480, 2490, 2492, 2053B, 2054B, 2055B, 81511, 81505, 81515, 81555		X		

DISCONTINUED PRODUCTS		RTTNA Specifications			
Product Name	Product Codes	1 Year	2 Years	4 Years	5 years
Pre-Buff Cleaners - Non Flammable Liquid	71		X		
Pre-Buff Cleaners - Non Flammable Spray	70		X		
Special Cement BL - Non Flammable	BL-8, BL-32, BL-G			X	
Cold Vulcanizing Fluid - Non Flammable	203, 204, 205			X	
OTR Special BL Cement	5576			X	
Thermopress MTR Solution	5578			X	
Repair Sealant - Non Flammable	76, 76G	X			
Bead Sealer - Non Flammable	960, 960ND			X	
A & B Compound - Non Flammable	50, 51		X		

Shelf Life Specifications were taken from current Technical Data Sheets available on the RTTNA website www.rematiptop.com

Product shelf life is specified from Date of Manufacture.

Shelf Life Specifications are based on storage in dry, dark, cool (15°C to 25°C; 60°F to 77°F) in unopened original packaging.