



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Tip Top Primer HG-2

Chemical Family: Polymer in Aromatic Hydrocarbon Solution

Product Use: Primer coating

Restrictions on Use: Use as directed by manufacturer

Distributed By: Rema Tip Top/North America, Inc
1500 Industrial Blvd.
Madison, GA 30650
Phone: 706-752-4000

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. HAZARD IDENTIFICATION

GHS Classifications

Health Hazards

Acute Toxicity, Inhalation, Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2A
Reproductive Toxicity, Category 2
Specific Target Organ Systemic Toxicity, Single Exposure, Category 2, Liver, Kidney, Bladder, Central Nervous System [Inhalation]
Aspiration Hazard, Category 1

Physical Hazards

Flammable Liquid, Category 3

Environmental Hazards

Chronic Aquatic Toxicity, Category 1



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

GHS-Labeling Pictograms:



Signal Word: **Danger!**

Hazard Statements

H226: Flammable liquid and vapor
H303: Can be harmful if swallowed
H304: May be fatal if swallowed and enters airways
H315: Causes skin irritation
H320: Causes eye irritation
H332: Harmful if inhaled
H336: May cause drowsiness or dizziness
H351: Suspected of causing cancer
H373: May cause damage to organs through prolonged or repeated exposure
H410: Very toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention:

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P233: Keep container tightly closed.
P235: Keep cool.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe vapors.
P263: Avoid contact during pregnancy/while nursing.
P264: Wash skin and exposed areas thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P281: Use personal protective equipment as required.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313: IF exposed or concerned: Get medical/advice attention.

P314: Get medical advice/attention if you feel unwell.

P321: Specific treatment found in supplemental First Aid section of this SDS (Section 4).

P332 + P313: If skin irritation occurs: Get medical advice/attention.

P337 + P313: If eye irritation persists: Get medical advice/attention.

P370 + P378: In case of fire: Use alcohol-resistant foam, carbon dioxide, or dry chemical for extinction.

P362: Take off contaminated clothing and wash before reuse.

P391: Collect spillage.

Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405: Store locked up

Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical characterization

Component*	CAS #	% By Wt.
Reaction mass of xylene and ethylbenzene	NA*	50 - 80
Alkanes, C14-C17, chloro	85535-85-9	< 10

*A blend of mixed xylenes and ethylbenzene

4. FIRST AID MEASURES

Inhalation

Symptoms & Effects: Nose, throat and respiratory tract irritation, nausea, headache, dizziness, drowsiness, shortness of breath, confusion

Measures: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, begin artificial respiration. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.

Skin Contact

Symptoms & Effects: Skin irritation, local redness, skin drying, skin cracking

Measures: Wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes while washing. If skin irritation develops, seek medical advice/attention. Wash contaminated clothing before reuse.



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

Eye Contact

Symptoms & Effects: Eye irritation, tearing, eye redness

Measures: Immediately rinse eyes with water for at least 15 minutes. Remove contact lenses after the initial few minutes and if easy to do so and resume rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while rinsing. If eye irritation persists, seek medical attention.

Ingestion

Symptoms & Effects: Mouth, throat and digestive tract irritation

Measures: Seek immediate medical attention. Do not induce vomiting unless instructed to do so by trained medical personnel. If the victim is drowsy or unconscious, do not give anything by mouth. Place individual on their left side and place their head down. Do not leave victim unattended.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical, Carbon dioxide, Water spray

Unsuitable Extinguishing Media: Direct water stream (See Precautions)

Hazardous Combustion Products: Aldehydes, Hydrocarbons, Carbon monoxide, Carbon dioxide

Protective Equipment for Fire-Fighters: Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Precautions for Fire-Fighters: Do not use direct water stream as this may spread fire. Use water spray to cool fire exposed containers and structures if this can be done with minimal risk. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Water fog, if applied gently, may be used as a blanket for fire extinguishment. Contain fire water run-off if possible, as it may cause environmental damage.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Recommended to wear chemical splash goggles & resistant gloves, such as polyvinyl alcohol-based gloves, and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

Personal Precautions: Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

Environmental Precautions: Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

Methods & Materials for Clean-Up: Contained spilled material with inert, non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth, polyethylene or polypropylene fibers, vermiculite, etc.). Remove residual material with soap and hot water. Use spark-proof tools and explosion-proof equipment for clean-up. Transfer to a suitable container for disposal according to proper federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, or solid), all hazard precautions given in this SDS must be observed. Application of a direct flame to a container of this product can cause an explosion and/or fire. Avoid use of electric band heaters as failures of electric band heaters can lead to fire. Take precautionary measures against static discharge.

Wear proper PPE when handling this product including protective gloves, chemical splash goggles, and impervious clothing. Avoid prolonged or repeated skin contact. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Emergency showers and eye wash stations should be readily accessible. Do not eat, drink or smoke when handling this product.

Storage: Store in a cool, well-ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up.

Incompatible Materials: Alkalis, Strong acids, Strong oxidizing agents

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits :

Exposure limits have not been established for this product.

Xylene	CAS # 1330-20-7	
OSHA	Permissible Exposure Limit (PEL)	100 ppm (435 mg/m ³)
ACGIH	Time weighted average (TWA)	100 ppm (435 mg/m ³)
NIOSH	Recommended Exposure Limit (REL)	100 ppm (435 mg/m ³)

Ethylbenzene	CAS # 100-41-4	
OSHA	Permissible Exposure Limit (PEL)	100 ppm (435 mg/m ³)
ACGIH	Threshold Limiting Value (TLV)	20 ppm (435 mg/m ³)
NIOSH	Recommended Exposure Limit (REL)	100 ppm (435 mg/m ³)

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. Provide readily accessible eye wash stations and safety showers.

Occupational Exposure Controls: Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Protective and Hygiene measures: Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

Eye Protection: Recommended to wear tight fitting, chemical splash goggles with side shields when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

Hand Protection: Recommended to wear suitable resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Suitable gloves will be based on product use and the period of use, and may include neoprene, butyl-rubber, nitrile rubber, etc.

Skin Protection: Recommended to wear impervious clothing, such as a fuller rubber suit and long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black Liquid

Odor: Aromatic

Odor Threshold: No data available

pH: No data available

Melting/Freezing point: < -53°F (< -47°C)

Boiling point/range: > 270°F (> 130°C)

Flash point (Tag closed cup): 77°F (25°C)

Evaporation rate: < 1.0 n-Butyl Acetate

Flammability: Lower Limit: 1.0% (V) **Upper Limit:** 6.7% (V)

Vapor pressure: No data available

Relative vapor density: > 3 (Air = 1)

Density: 0.95 g/cm³ (7.9 lbs/gal) @ 68°F (20°C)

Solubility in water: Immiscible

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

Ignition temperature: 810°F (430°C)
Decomposition temperature: No data available
Viscosity (dynamic): No data available

10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Product will not undergo hazardous polymerization.

Conditions to Avoid: Heat, Flames, Sparks, Ignition sources

Incompatible Materials: Alkalis, Strong acids, Strong oxidizing agents

Hazardous decomposition products: Aldehydes, Hydrocarbons, Carbon monoxide, Carbon dioxide

11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion

Symptoms Related to Physical, Chemical and Toxicological Characteristics: Nose, throat and respiratory tract irritation, skin irritation, local redness, skin drying, skin cracking, allergic skin reactions, eye irritation, tearing, eye redness, mouth, throat and digestive tract irritation.

Delayed and Immediate Effects & Chronic Effects from Exposure: With repeated exposure, the substance may have effects on the central nervous system, kidneys, blood and liver. This substance is suspected of causing central nervous system depression, with effects such as dizziness and drowsiness. This substance is a potential carcinogen to humans as outlined by OSHA, IARC, and ACGIH (see below).

Measures of Toxicity:

Acute toxicities are calculated based on component toxicities

Mixture: ATE Dermal Toxicity: ~ 1,550 mg/kg

ATE Inhalation Toxicity: ~ 15 mg/l 4h

Xylene

Acute Oral Toxicity

Acute Dermal Toxicity

Acute Inhalation Toxicity

CAS # 1330-20-7

LD₅₀ Rat: 4,300 mg/kg

LD₅₀ Rabbit: > 1,700 mg/kg

LC₅₀ Rat: 5,000 ppmV

Ethylbenzene

Acute Dermal Toxicity

CAS # 100-41-4

LD₅₀ Rabbit: 15,433 mg/kg



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

Carcinogen Claims:

OSHA: **Yes**; International Agency for Research on Cancer (IARC): **Yes; 2A [Probably Carcinogenic to Humans]**, ACGIH: **No; A3 [Animal Carcinogen, not likely in Humans]**

National Toxicology Program (NTP) Report on Carcinogens: **II; [Reasonably Anticipated]**

12. ECOLOGICAL INFORMATION

Eco-toxicity: This substance is expected to be very toxic to aquatic organisms with long lasting effects. It is strongly advised that this substance does not enter the environment. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Xylene

CAS # 1330-20-7

Toxicity to Fish LC₅₀ – 23.53 mg/l (Fathead Minnow; 96 h)
Toxicity to Daphnia EC₅₀ > 100.0 mg/l (Water flea; 24 h)

Ethylbenzene

CAS # 100-41-4

Toxicity to Fish LC₅₀ – 4.2 mg/l (Rainbow Trout; 96 h)
LC₅₀ – 9.1 mg/l (Fathead Minnow; 96 h)
Toxicity to Daphnia EC₅₀ – 1.37 mg/l (Water Flea; 48 h)
Toxicity to Algae EC₅₀ – 3.6 mg/l (Green Algae; 96 h)

Persistence & Degradability: No data available

Bio-accumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No data available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.
Contaminated packaging should be emptied as far as possible before disposal.

14. TRANSPORT INFORMATION

DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1133

PROPER SHIPPING NAME: Adhesives, containing a flammable liquid (Xylene, Ethylbenzene)

TRANSPORTATION HAZARD CLASS: 3

PACKING GROUP: III

HAZARD LABEL: 3



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 3

UN NUMBER: UN1133

MARINE POLLUTANT: Yes

EmS: F-E, S-D

IMDG PACKING GROUP: III

HAZARD LABEL: 3

Description of the goods

ADHESIVES, CONTAINING A FLAMMABLE LIQUID (Xylene, Ethylbenzene)

IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 3

UN NUMBER: UN1133

HAZARD LABEL: 3

Description of the goods

Adhesives, containing a flammable liquid (Xylene, Ethylbenzene)

15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

SARA Title III

Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed*

Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part

Component	CAS #	Weight %	CERCLA RQ
Xylene	1330-20-7	65 - 80	100
Ethylbenzene	100-41-4	10 - 20	1,000

OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements, Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

CANADIAN REGULATIONS

WHMIS Classification: Same as OSHA GHS



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994


SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

STATE REGULATIONS

California Proposition 65

WARNING:  This product contains ethylbenzene which is known to the State of California to cause cancer. For more information go to, www.P65warnings.ca.gov

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List/Permissible Exposure List

California Toxic air contaminants

Connecticut Permissible Exposure Limits

Delaware List of Chemicals and RQs

Hawaii Permissible Exposure Limits

Idaho Toxic Air Pollutants

Illinois Toxic Air Contaminants List

Louisiana Toxic Air Pollutants

Maine Hazardous Air Pollutants

Maryland Toxic Air Pollutants for Existing Sources

Massachusetts Hazardous Substances List

Michigan Permissible Exposure Limits

Minnesota Hazardous Substances

Minnesota Permissible Exposure Limits

Nebraska Hazardous Air Pollutants

New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List

New York List of Hazardous Substances

Ohio Toxic Air Contaminants

Oklahoma Toxic Air Contaminants

North Carolina TAP Emissions Rates Requiring a Permit

Pennsylvania Hazardous Substances List

Rhode Island Toxic Air Contaminants

Tennessee Permissible Exposure Limits

Vermont Hazardous Air Contaminants/Permissible Exposure Limits

Washington Permissible Exposure Limits for Airborne Contaminants.

West Virginia Toxic Air Pollutant List

Wisconsin hazardous Air Contaminants

Note: Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.



Safety Data Sheet

REMA Tip Top

Product #s: 5250970, 5252987, 52529994

SDS #: RTT-IND-047

Rev. # 5

Rev. Date: 3/16/2020

16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
800-424-9300

FOR ANY OTHER INFORMATION:

REMA TIP TOP/NORTH AMERICA, INC
240 Pegasus Avenue, 2nd Floor
NORTHVALE, NJ 07647
201-256-8200

NOTICE: REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.