



 C max. inch (mm)	PR PLY RATING	10-14	16-20	22-26	28-32	34-38	40-44	46-50	52-58	60-
1/2 (15)	PN No.	050	050	050	050	050+	050+	050+	050+	050+
1 (25)	PN No.	050	050	050	050+	050+	050+	050+	052	052
2 (50)	PN No.	050	050	050	050+	052	052	052+	054	054
3 (75)	PN No.	050	050+	052	052	052	052+	054	054+	056
4 (100)	PN No.	052	052	052	052+	054	054+	056/052+	056/052+	056/052+
5 (125)	PN No.	052	052+	052+	054	054+	056+	056/052+	056+/054	056+/054+
6 (150)	PN No.	054	054	054	054+	054+	056/052	056+/054	056+/054	058/056
7 (175)	PN No.	054	054	054	054+	056+	056+/052	058+/054	058+/054	058+/056
8 (200)	PN No.	-	054	056	056+	058+	056+/052	058/056	058+/056	060/056+

2

 C max. inch (mm)	PR PLY RATING	10-14	16-20	22-26	28-32	34-38	40-44	46-50	52-58	60-
9 (225)	PN No.	-	-	056	056+	058+	058/054	058+/056	060/056	060/056+
10 (250)	PN No.	-	-	056	056+	058/052	058/054	060/056	060/056+	060/056+

Non penetrating injury (up to 50%)

 C max. inch (mm)	PR PLY RATING	10-14	16-20	22-26	28-32	34-38	40-44	46-50	52-58	60-
2 (50)	PN No.	050	050	050	050+	052	052	052+	052+	052+
4 (100)	PN No.	050	050	052	052	052+	052+	054	054+	054+
6 (150)	PN No.	052	052	054	054	054	054	054+	054+	056+
8 (200)	PN No.	-	054	054	054	054	056+	056	056+	058+
10 (250)	PN No.	-	-	054	056	056	056+	056+	058	058+

